


Lutze TOP-T Fittings NPT

Plastic NPT



Characteristics:

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- Temperature range -30°C - +80°C/
-22°F - +176°F
- Max temporary temperature
up to +150°C/+300°F
- Protection class IP68

Fitting Specifications:

Connecting thread NPT
 Material Polyamide 6
 Seal Neoprene
 Color Black RAL 9005
 Gray RAL 7001

Part No.	Thread	Clamping Range Ø inch	Clamping Range Ø mm	TL mm	D/SW mm	TD mm	H mm
BLACK							
FPNPT38B	NPT 3/8"	0.197-0.394	5-10	15	22	16.5	28
FPNPT12B	NPT 1/2"	0.394-0.551	10-14	15	27	20.7	31
FPNPT34B	NPT 3/4"	0.511-0.709	13-18	15	33	25.9	35
FPNPT10B	NPT 1"	0.709-0.984	18-25	18	42	32.4	40
GRAY							
FPNPT38G	NPT 3/8"	0.197-0.394	5-10	15	22	16.5	28
FPNPT12G	NPT 1/2"	0.394-0.551	10-14	15	27	20.7	31
FPNPT34G	NPT 3/4"	0.511-0.709	13-18	15	33	25.9	35
FPNPT10G	NPT 1"	0.709-0.984	18-25	18	42	32.4	40
REDUCED CLAMPING RANGE							
FPNPT38B-R	NPT 3/8"	0.118-0.276	3-7	15	22	16.5	28
FPNPT12B-R	NPT 1/2"	0.276-0.472	7-12	15	27	20.7	31
FPNPT34B-R	NPT 3/4"	0.354-0.630	9-16	15	33	25.9	35
FPNPT10B-R	NPT 1"	0.472-0.787	12-20	18	42	32.4	40