

Lutze TOP-T Fittings Pg ●

Plastic Pg



Part No.	Thread A	Clamping Range Ø C	L mm	SW1 mm	SW2 mm	H mm
FITTINGS BLACK						
FPPG7B	Pg 7	3-6.5	8	15	15	30.5
FPPG9B	Pg 9	4-8	8	19	19	34
FPPG11B	Pg 11	5-10	8	22	22	37
FPPG13B	Pg 13.5	6-12	9	24	24	39
FPPG16B	Pg 16	10-14	10	27	27	42.5
FPPG21B	Pg 21	13-18	11	33	33	47.5
FPPG29B	Pg 29	18-25	11	42	42	53
FPPG36B	Pg 36	22-32	13	53	53	61
FPPG42B	Pg 42	30-38	13	60	60	65
FPPG48B	Pg 48	34-44	14	65	65	67

FITTINGS GRAY						
FPPG7G	Pg 7	3-6.5	8	15	15	30.5
FPPG9G	Pg 9	4-8	8	19	19	34
FPPG11G	Pg 11	5-10	8	22	22	37
FPPG13G	Pg 13.5	6-12	9	24	24	39
FPPG16G	Pg 16	10-14	10	27	27	42.5
FPPG21G	Pg 21	13-18	11	33	33	47.5
FPPG29G	Pg 29	18-25	11	42	42	53
FPPG36G	Pg 36	22-32	13	53	53	61
FPPG42G	Pg 42	30-38	13	60	60	65
FPPG48G	Pg 48	34-44	14	65	65	67

REDUCED CLAMPING RANGE						
FPPG7G-R	Pg 7	2-5	8	15	15	30.5
FPPG9G-R	Pg 9	2-6	8	19	19	34
FPPG11G-R	Pg 11	3-7	8	22	22	37
FPPG13G-R	Pg 13.5	5-9	9	24	24	39
FPPG16G-R	Pg 16	7-12	10	27	27	42.5
FPPG21G-R	Pg 21	9-16	11	33	33	47.5
FPPG29G-R	Pg 29	12-20	11	42	42	53
FPPG36G-R	Pg 36	20-26	13	53	53	61

LOCKNUTS BLACK						
LPPG7B	Pg 7			19		5
LPPG9B	Pg 9			22		5
LPPG11B	Pg 11			24		5
LPPG13B	Pg 13.5			27		6
LPPG16B	Pg 16			30		6
LPPG21B	Pg 21			36		7
LPPG29B	Pg 29			46		7
LPPG36B	Pg 36			60		8
LPPG42B	Pg 42			65		8
LPPG48B	Pg 48			70		8

LOCKNUTS GRAY						
LPPG7G	Pg 7			19		5
LPPG9G	Pg 9			22		5
LPPG11G	Pg 11			24		5
LPPG13G	Pg 13.5			27		6
LPPG16G	Pg 16			30		6
LPPG21G	Pg 21			36		7
LPPG29G	Pg 29			46		7
LPPG36G	Pg 36			60		8
LPPG42G	Pg 42			65		8
LPPG48G	Pg 48			70		8

Characteristics:

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- Temperature range -20°C - +100°C / +14 - +212 F
- Protection Grade IP68 – 5 bar

Fitting Specifications:

Dome nut	Polyamide PA6 V-2
Sealing Ring	Polychloroprene-Nitrile rubber CR/NBR
Gland body	Polyamide PA6 V-2
Connecting thread	Pg as per DIN 40430
Color	Black Gray RAL 7001

Locknut specifications:

- For secure tightening of cable glands and accessories
- Hexagonal locknut Polyamide PA6 GF30
- Internal thread Pg as per DIN 40430

1-800-447-2371 – www.lutze.com

