

## FR-9 – Polyester – Acrylic Adhesive

- Conformable, strong polyester coated with a high quality solvent based acrylic adhesive.
- Available in a variety of colors for coding and marking during application.
- Excellent for outer wrapping on capacitors and coils, holding transformer construction & wire harness bundling.
- Flame retardant complies with requirements of UL 510.
- Insulation class: 130°C (266°F)
- Dielectric strength 5,000 volts.
- Tape Thickness: 2.3 mil Tensile Strength: 25 lb/in
  Adhesion: 35 oz/in Elongation: 100%
- Wound on 3" ID plastic core.



## 149 - Polyester - Thermoset Rubber Adhesive - Yellow

- Conformable, strong polyester coated with a high quality solvent based rubber adhesive.
- Thermoset properties of the adhesive ensures permanent and strong bond to a variety of surfaces.
- Insulation Class: 130°C (266°F)
- UL Listed.
- Standard color: yellow.
- Tape Thickness: 2.3 mil Adhesion: 80 oz/in Tensile Strength: 25 lb/in Elongation: 45%
- Wound on 3" ID plastic core.

## 194 – Polyester – Metalized – Acrylic Adhesive – Silver

- Thin, yet conformable, polyester coated with a quality solvent based acrylic adhesive.
- Excellent chemical and thermal stability.
- Designed primarily for non-electrical applications.
- Used for reflective shielding.
- Shiny, vibrant surface great in decorative trim and graphic arts applications.
- Standard color: silver.
- Tape Thickness: 2.2 mil Adhesion: 45 oz/in Tensile Strength: 24 lb/in Elongation: 100%
- Wound on 3" ID plastic core.



Series	Product Code	Size	Units/Case	Pack	Features
FR-9	COLORS: white(0), yellow(1), clear(2), black(3), red(4)			Excellent for outer wrapping on capacitors	
18	18_00-2500	1/4" (6.3 mm) x 72 y	rd roll	bagged	and coils, holding transformer construction & wire harness bundling.
	18_00-3750	3/8" (9.5 mm) x 72 y	rd roll	bagged	a wife fluriess boliding.
	18_00-5000	1/2" (12.7 mm) x 72 y	roll roll	bagged	
	18_00-7500	3/4" (19.0 mm) x 72 y	rd roll	bagged	
	18_01	1" (25.4 mm) x 72 y	roll roll	bagged	
149 <sup>♣</sup>	19900-2500	1/4" (6.3 mm) x 72 y	roll	bagged	Universal workhorse for bobbin wound coil covers, start wire anchor for stick wound transformer, lead wire anchor and hold down and small motor end turn bundling.
	19900-3750	3/8" (9.5 mm) x 72 y	roll	bagged	
	19900-5000	1/2" (12.7 mm)x 72 y	roll	bagged	
	19900-7500	3/4" (19.0 mm)x 72 y	roll	bagged	
	19901	1" (25.4 mm)x 72 y	roll roll	bagged	
194	19400-2500	1/4" (6.3 mm) x 72 y	roll	bulk	Reflective surface makes this tape suitable for web splices that utilize photo-sensing detection equipment.
8	19400-5000	1/2" (12.7 mm)x 72 y	roll	bulk	
	19400-7500	3/4" (19.0 mm)x 72 y	roll	bulk	
	19401	1" (25.4 mm)x 72 y	rd roll	bulk	
	19402	2" (50.8 mm)x 72 y	roll	bulk	
	L194	38.4" (975 mm) x 72 y	rd log	bulk	