Technical Data Sheet:	DS061/0517
Product Description	Straight flange fittings for Large diameter corrugated flexible conduit
Product Range	LDMP and LDMPS Large diameter conduit fittings



Material; Nylon PA6

Colour: Black or Grey

FLEXIBLE CONDUIT SOLUT

Roman Way, Coleshill Birmingham **B46 1HG**


Tel: 00 44 (0)1675 466900 Website: www.flexicon.uk.com



LDMP Conduit Fitting







Nominal Size	Part No	Nominal Dimensions (mm)							
Non		Α	В	С	D	Е	F	G	Ø
80	LDMP-80-FL	60	80	94	52	7.5	106	96	70
106	LDMP-106-FL	74	108	126	52	7.5	132	126	95

IP Rating:

• IP40 with LDMP fittings

Fire Performance: Self extinguishing, halogen, sulphur and phosphorous free

• IP65 with LDMPS fittings

Applications:

Ideal for use in both internal and external applications large diameter corrugated conduit provides excellent resistance to abrasion, oil and solvents.

Typical Applications: Machines and large control cabinets.

Compression Strength:

Contact Flexicon

Pull-off (Tensile) strength:


Contact Flexicon

Temperature Performance:

Static: -40°C to +120°C

LDMPS Conduit Fitting





Nominal Size	Part No	Dimensions (mm)							
Non		Α	В	С	D	Е	F	G	Ø
80	LDMPS-80-FL	60	80	94	52	7.5	106	96	70
106	LDMPS-106-FL	74	108	126	52	7.5	132	126	95

Compliance, Approvals & Accreditation;







Typical Applications;



Machinery and OEM's

Errors, omissions and amendments excepted. As part of continuing product development Flexicon Ltd reserve the right to alter product specifications without prior notice. Data given is correct at time of compilation. Product specification and application data is for guidance only and does not constitute a warranty of any kind, either expressed or implied for Flexicon products or their suitability for a specific purpose. Third party approvals maybe limited to certain sizes within a product range.

Created by;	Approved by;	Date;	Page Number;
Sarah Lee - Marketing Assistant	lan Gibson - Technical Director	May 2017	Page 1 of 1