

# Conduit Application Guide

	Conduit Type	Page	Flexibility				Metal Used	Plastic Used	High Mech. Strength	Listed for Direct Burial	Halogen-Free	Low Fire Hazard	Accepts Standard Liquidtight Fittings	Self-Extinguish	EMI / RFI Shielding	Approval
			Continued Flexing	Small Bend Radius	Flexible	Pliable (Static)										
Jacketed Metallic	TYPE LA	7			•		Steel	PVC	•	•			•	•		UL SF
	TYPE LT	8		•	•		Steel	PVC					•			JIC
	TYPE LTFG	9		•	•		Steel	PVC					•			NSF/FDA
	TYPE EF	10		•	•		Steel	PVC					•			JIC
	TYPE LOR	10		•	•		Steel	PVC					•			JIC
	TYPE CBLA	11			•		Steel	PVC	•	•			•	•		UL SF
	TYPE CSA	12			•		Steel	PVC	•				•	•		SF
	TYPE ATLA	13			•		Steel	PVC	•	•			•	•		UL SF
	TYPE AT	14		•	•		Steel	PVC					•			
	TYPE ATX	14		•	•		Steel	TPR			•		•			
	TYPE VJC	15		•	•	•	Steel	PVC					•			
	TYPE ALT	15			•		Aluminum	PVC					•			
	TYPE ZHLA	16			•		Steel	PU	•	•	•	•	•	•		UL
	TYPE CEA	17			•		Steel	PU			•	•	•	•		
TYPE ACEA	18			•		Aluminum	PU			•	•	•	•			
EMI / RFI	TYPE SLA	22			•		Steel	PVC	•	•	Available	Available	•	•	•	UL
	TYPE EMS	23			•		Bronze	PVC			Available	Available	•	•	•	
	TYPE EMCS	23			•		Bronze	PVC			Available	Available	•	•	•	
Unjacketed Metallic	TYPE BR	25			•		Steel		•							UL SF 3/8
	TYPE ABR	26			•		Aluminum									UL SF 3/8
	TYPE ABRH	27			•		Aluminum		•							SF
	TYPE FSC	27			•		Steel		•							
	TYPE USL	28		•	•		Steel									RA
	TYPE UG	28			•	•	Steel									
	TYPE SL	29		•	•	•	Steel									
	TYPE PF	30			•		Steel									UL
Nonmetallic	CORRLOK®	32	•	•	•			Nylon	•		•	•	•			RA
	TYPE LNM-P	33	•		•			PVC					FNMC-A	•		UL • UL
	TYPE NM	34			•			PVC	•	•			•	•		UL SF
	TYPE NMHT	34			•			PVC	•	•			•	•		UL SF
	TYPE NM2	35	•		•			PVC					•	•		RA

Shield-Flex, SLA, EMS, EMCS, HFSLA, HFEMS & HFEMCS are trademarks of Electri-Flex Company, registered in the U.S. Patent and Trademark Office.