



G3V-STM | P/C HD ST MID-MID GREEN 3'

Body Features

| | |
|-------------------|-------|
| Color | Green |
| Conductor Plating | Gold |

Configuration Features

Number of Connectorized Ends 2

Contact Features

| | |
|------------------------|------|
| Center Contact Plating | Gold |
|------------------------|------|

Dimensions

Cable Assembly Length 0.93 m | 3.051 ft

Electrical Characteristics

| | |
|---------------------|--------|
| Connector Impedance | 75 ohm |
| Impedance | 75 ohm |
| Voltage | 600 V |

Operation/Application

For Use With All WECO Midsize 2x32 Panels

Product Availability

| | |
|--------------------|---------------|
| Region | North America |
| Applicable Country | Not Specified |

Product Type Features

| | |
|------------------------|-----------------------------------|
| Product Type | Cable Assembly |
| Assembly Type | WECO Midsize Plug to Midsize Plug |
| Connector Type (End A) | Midsize |
| Connector Type (End B) | Midsize |
| Cable Assembly Type | Midsize to Midsize |
| Cable Type | Coaxial |
| Coaxial Cable Type | RG 59 |
| Product Category | Broadcast Video |
| Product Designation | Patch Cord |
| Product Line | Broadcast |
| RF Connector Type | Video Jacks |

G3V-STM | P/C HD ST MID-MID GREEN 3'

Shielded Yes

Usage Conditions

Operating Temperature Range -40 – 65 °C

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant