

Diesel Locomotive Cable 2000 Volts (EPR/XL-CPE)

UL Types RHH/RHW-2 2000 V and C(UL) RW90 1000 V

Flexible, Oil-, Sunlight- and Ozone-Resistant, Flame-Retardant, -40°C to 90°C



Compliances:

Industry Compliances:

- Type RHH/RHW-2 per UL 44, UL File # E90494
- c(UL)US Type RW90 per CSA C.22.2-38, UL File # E90494
- National Electrical Code (NEC)
- ICEA S-95-658/NEMA WC70
- "For CT Use" on 1/0 AWG and larger in accordance with NEC®
- Accepted for listing as flame resistant by MSHA
- RoHS Compliant

Flame Test Compliances:

- UL 2556 VW-1
- IEEE 1202/CSA FT4 for sizes 1/0 AWG and larger

Product Construction:

Conductor:

- 14 AWG (2.08 mm) thru 1111.1 kcmil (562 mm) Class I fully annealed flexible stranded tin coated copper per AAR 589

Insulation:

- Flame-retardant, lead-free Cross-linked Ethylene Propylene (EP) with separator tape over the conductor to facilitate stripping

Jacket:

- Black, flame-retardant, sunlight-, ozone- and oil-resistant, lead-free Cross-linked Chlorinated Polyethylene (XL-CPE)
- Colors available upon request

Print:

- GENERAL CABLE® (MFG LOCATION) DIESEL LOCOMOTIVE 2000 V P-07-KA120005-MSHA C(UL)US TYPE RHH OR RHW-2 VW-1 (SIZE) AWG/kcmil (MM²) EP FOR CT USE* SR -40°C FT4 OR RW90 EP 1000 V ROHS MONTH/YEAR OF MFG SEQUENTIAL FOOTAGE MARK

*Applicable for sizes 1/0 AWG and larger only

Applications:

- For use up to 2000 V as power cables in wind turbine generator applications per UL Subject 6140
- Diesel electric locomotives
- Mining and earth-moving equipment
- General purpose use as flexible power leads
- Flexible power leads in cable trays in sizes 1/0 AWG and larger
- Accepted for listing as flame-resistant by MSHA

Features:

- Rated 90°C wet or dry per UL 44/CSA C.22.2-38
- Flexible tinned copper stranding
- Excellent resistance to oils, gear lubricants, ozone, sunlight, heat and flame
- Designed to withstand continuous flexing

Minimum Bend Radius:

- 8X O.D. for fixed installations

Torsion Requirements:

- +/-180° twists per meter for 5,000 cycles at -40°C with cable weight compensated to 18 meters

AC Withstand Voltage Testing requirements per UL 44:

14 - 10 AWG	6000 V
8 - 2 AWG	7500 V
1 - 4/0 AWG	9000 V
262.6 kcmil - 444 kcmil	10000 V
535.3 kcmil - 929.9 kcmil	11000 V
1111.1 kcmil	13500 V

CATALOG NUMBER	COND. SIZE		COND. STRAND	NOMINAL COND. O.D.		NOM. INS. THICKNESS		JACKET THICKNESS		NOMINAL O.D.		APPROX. NET WEIGHT	
	AWG/kcmil	mm²		INCHES	mm	INCHES	mm	INCHES	mm	INCHES	mm	LBS/1000 FT	kg/km
14 AWG - 1111.1 kcmil CONDUCTORS													
5310.01014	14	2.08	19W	0.070	1.8	0.045	1.1	0.015	0.4	0.20	5.1	30	45
5310.01012	12	3.31	19W	0.088	2.2	0.045	1.1	0.015	0.4	0.22	5.6	39	58
5310.01010	10	5.26	27W	0.117	3.0	0.045	1.1	0.015	0.4	0.25	6.4	56	83
5310.01008	8	8.36	37W	0.144	3.7	0.055	1.4	0.030	0.8	0.33	8.3	87	129
5310.01006	6	13.3	61W	0.190	4.8	0.060	1.5	0.030	0.8	0.38	9.7	131	195
5310.01004	4	21.1	105W	0.262	6.7	0.060	1.5	0.030	0.8	0.46	11.7	202	301
5310.01002	2	33.6	158W	0.315	8.0	0.060	1.5	0.030	0.8	0.51	13.0	285	424
5310.01001	1	42.4	224W	0.375	9.5	0.080	2.0	0.045	1.1	0.64	16.3	417	621
5310.01110	1/0	53.5	280W	0.435	11.0	0.080	2.0	0.045	1.1	0.70	17.8	494	735
5310.01210	2/0	67.4	329W	0.465	11.8	0.080	2.0	0.045	1.1	0.73	18.5	587	874
5310.01310	3/0	85	456W	0.535	13.6	0.080	2.0	0.045	1.1	0.80	20.3	718	1069
5310.01410	4/0	107	551W	0.581	14.8	0.080	2.0	0.045	1.1	0.84	21.3	845	1258
5310.01262	262.6	133	650W	0.617	15.7	0.090	2.3	0.065	1.7	0.94	23.9	1050	1563
5310.01313	313.1	158	777W	0.671	17.0	0.090	2.3	0.065	1.7	1.00	25.3	1195	1778
5310.01373	373.7	189	925W	0.735	18.7	0.090	2.3	0.065	1.7	1.06	26.9	1384	2060
5310.01444	444.4	225	1110W	0.786	20.0	0.090	2.3	0.065	1.7	1.11	28.2	1634	2432
5310.01535	535.3	271	1332W	0.877	22.3	0.090	2.3	0.065	1.7	1.20	30.5	1925	2865
5310.01646	646.4	327	1609W	0.960	24.4	0.090	2.3	0.065	1.7	1.29	32.8	2307	3433
5310.01777	777.7	394	1924W	1.054	26.8	0.090	2.3	0.065	1.7	1.38	35.1	2728	4060
5310.01929*	929.9	475	2318W	1.230	31.2	0.090	2.3	0.065	1.7	1.56	39.6	3570	5313
5310.01111*	1111.1	562	2745W	1.328	33.7	0.115	2.9	0.095	2.4	1.77	44.9	4232	6298