

TABLE OF CONTENTS

- A. GENERAL INFORMATION
- B. APPLIANCE WIRE
 - 1. Appliance Wire (PVC)
 - Machine Tool Wire, Dual Rated, UL-1015/1230/TEW
 - Lead Wire, UL-1007, UL-1028
 - UL-1056, UL-1060
 - 2. Appliance Lead Wire (XLPE)
 - UL-3173, 3915, 3196
 - UL-3199
 - UL-3237, 3290
 - UL-3321
 - 3. Appliance Lead Wire (Neoprene) NO LONGER AVAILABLE
UL-3039, 3044, 3046
 - 4. Appliance Lead Wire (EPDM) NO LONGER AVAILABLE
UL-3284, 3328, 3340, 3484, 3556
 - 5. Hermetic Lead Wire
 - UL-5170 (DMD)
 - UL-5058 (DTMD)
- C. AUTOMOTIVE WIRE & CABLE
 - 1. Automotive Primary Wire (PVC)
 - GPT (General Purpose Thermoplastic)
 - HDT, HTP (Heavy Duty Thermoplastic)
 - TWP (Thin Wall Thermoplastic)
 - UTP (Ultra-Thin Wall Thermoplastic)
 - 2. Automotive Primary Wire (XLPE)
 - GXL (General Purpose Crosslink)
 - SXL (Special Purpose Crosslink)
 - TXL (Thin Wall Crosslink)
 - UXL (Ultra-Thin Wall Crosslink)
 - 3. Automotive Battery Cable
 - SGT (PVC)
 - SGX (XLPE)
 - STX (Thin Wall XLPE)
- D. MARINE WIRE
 - Marine Wire (PVC)
 - Marine Battery Cable (SGT)
- E. CONSTRUCTION WIRE (XLPE)
 - XHHW, XHHF
 - RHH, USE, RHW
- F. SWITCHGEAR WIRE (XLPE)
 - SIS
 - SIS-F (VW-1 Rating)
- G. MULTI-CONDUCTOR CABLE (PVC Jacket)
 - Trailer Cable
 - Boat Cable



ORDERING INFORMATION

PART NUMBER

GXL - 16 - 19 - B - xx
 Product Type Gauge Stranding Coating Specialty Code

Product Type: Type as referenced on catalog page (GXL, TWP,3321, etc.)
 Gauge: Wire gauge (16, 1/0, etc.)
 Stranding: Number of strands (19, 133, etc.) or special number (1000, 1010, etc.)
 Coating: "B" for bare copper or "T" for tinned copper
 Specialty Code: See customer service for designation

PACKAGING

Reels: Wood, Non-returnable
 12R - 12" Reel
 15B - 15" X 10", 1-9/16" Arbor
 16B - 16" x 12"
 18A - 18" x 14", 2" Arbor
 18B - 18" x 14", 1-9/16" Arbor
 18C - 18" x 14", 2" Arbor, 3/4" Flange
 24R - 24" Reel, 2" Arbor
 30A - 30" x 14", 2" Arbor
 30B - 30" Reel, 1-1/2" Flange

Reels: Wood, Non-returnable
 30R - 30" x 14", 1-9/16" Arbor
 36A - 36" x 12", 2" Arbor
 36B - 36" x 14", 3" Arbor

Drums: Fiber, Non-returnable
 35D - 35 Gallon, 20" high x 23" diameter
 55D - 55 Gallon, 30" high x 23" diameter
 75D - 75 Gallon, 42" high x 23" diameter

ACCEPTANCE OF ORDERS:

All orders are subject to written acceptance by Therm-O-Link, Inc. / Vulkor, Inc.

CREDIT:

All orders are subject to credit approval.

PRICING:

Material will be invoiced at the price in effect at the time of shipment.

TERMS OF PAYMENT:

Net 30 days cash.

FREIGHT TERMS:

Prices are FOB factory, shipped collect, unless otherwise stated.

QUANTITY VARIATION:

The quantity shipped against any item on an order is subject to a variation of +/- 10%.

WARRANTY:

Therm-O-Link, Inc. / Vulkor, Inc. warrants that the wire furnished is free from defects in material and workmanship. There is no other warranty expressed or implied.

RETURN POLICY:

No material will be accepted for return without prior written authorization.

AUTOMOTIVE PRIMARY WIRE

AUTOMOTIVE Revised Nov.2009

General Purpose Thermoplastic:
Polyvinyl chloride (PVC) insulated
wire manufactured to SAE J1128
standards to meet the following
specifications:

FORD: M1L 56A
CHRYSLER: MS-3450

GPT Bare Copper 80°C 60 Volts

| Product | #CU/MFT | Stranding | Wall Thickness | Min Order |
|-------------|---------|-----------|----------------|-----------|
| GPT-20-7-B | 3.46 | 7/0126 | .023 | 55M |
| GPT-18-16-B | 4.94 | 16/0098 | .023 | 45M |
| GPT-18-61-B | 4.90 | 61/36 | .023 | 50M |
| GPT-16-19-B | 7.40 | 19/0113 | .023 | 30M |
| GPT-16-37-B | 7.15 | 37/32 | .023 | 40M |
| GPT-14-19-B | 11.90 | 19/0142 | .023 | 22M |
| GPT-12-19-B | 18.35 | 19/0117 | .026 | 23M |
| GPT-10-19-B | 29.40 | 19/0224 | .031 | 28M |
| GPT-8-19-B | 48.00 | 19/0282 | .037 | 25M |
| GPT-6-49-B | 80.75 | 49/0232 | .045 | 50M |
| GPT-6-37-B | 82.00 | 37/0266 | .045 | 20M |
| GPT-4-61-B | 122.00 | 61/0249 | .045 | 20M |
| GPT-4-133-B | 122.00 | 133/0170 | .045 | 20M |

DELPHI PACKARD: ESM-3012

GPT Bare Copper 80°C 60 Volts

| Product | #CU/MFT | Stranding | Wall Thickness | Min Order |
|------------|---------|-----------|----------------|-----------|
| GPT-0.5-MM | 3.46 | 7/0126 | .023 | 55M |
| GPT-0.8-MM | 4.94 | 16/0098 | .023 | 45M |
| GPT-1.0-MM | 7.40 | 19/0113 | .023 | 30M |
| GPT-2.0-MM | 11.90 | 19/0242 | .023 | 22M |
| GPT-3.0-MM | 18.35 | 19/0177 | .026 | 23M |
| GPT-5.0-MM | 29.40 | 19/0224 | .031 | 28M |
| GPT-8.0-MM | 48.00 | 19/0282 | .037 | 25M |

Minimum order requirement reflects quantity per color, per release.
Different color quantities may be combined to determine pricing
with solid colors treated separately from striped colors.

800-776-9223 (Ohio) 800-684-7823 (Texas)