

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Spec ID: 4/CB- 100318
Spec Revision Level: New

Description: 4 Conductor **Bonded Cable** with 4 / GPT 18 GA Inners,
PVC 85 Deg C

(4) Inners: GPT-18-1015 (Wht)
GPT-18-1015 (Brn)
GPT-18-1015 (Yel)
GPT-18-1015 (Dgr)

Inners:

Stranding: 16 x .0098" Bare Copper, Lay =1.5"
Insulation OD: 0.097 inches +/- 0.002 inches
Wall Thickness: .023 inches (Nominal)
PVC Insulation: PVC 85 DegC Compound

Bonded Cable:

Max Height : 0.096 inches
Nom Height: 0.093 inches
Min Height : 0.090 inches
Max Width : 0.386 inches
Nom Width: 0.377 inches
Min Width : 0.368 inches
Surface Print: None

Specification Reference Data

SAE: J-1128

Ford: N/A

Chrysler: N/A

UL : N/A

CSA: N/A

Packard: N/A

Other:

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain

Title: Corporate Engineer

Dated: 1-26-2017