



ATLAS WIRE CORPORATION
9525 RIVER STREET
SCHILLER PARK, IL 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



ATLAS WIRE CORPORATION
REGISTERED TO ISO9001:2000
CERTIFICATE NO. A4894

MATERIAL SPECIFICATION SHEET

#14 19/0141 BC .023" PVC
ROHS COMPLIANT
AUTOMOTIVE PRIMARY WIRE
SAE J1128 – 105c TYPE GPT

CONDUCTOR: #14 19/0141 BC 1-1/2" LAY BUNCHED
NOMINAL O.D. .071"
APPROXIMATE CIRCULAR MILL AREA 3,777
WEIGHT PER THOUSAND FEET 11.75#
BASIC SPECIFICATION ASTM B 174

PVC: TEMPERATURE RATING 105c
ELONGATION 330% AVERAGE
SPECIFIC GRAVITY 1.35
DUROMETER (SHORE) 92 (A)
TENSILE STRENGTH 2850 PSI
OXYGEN INDEX 29
BRITTLE POINT -25c
SPARK TESTED 8,000 VOLTS
NOMINAL FINISHED O.D. .117"
WEIGHT PER THOUSAND FEET 15.84#