

PVC/PVC - Type GPT Marine Flat Multi-Conductor

Flat Jacketed Boat Cable, Trailer Cable

UL: 105°C, 75°C Wet, 600V, 1426, BC-5W2



| IEWC Part Number | AWG | No. of Conductors | Stranding | Nominal Insulation Thickness | | Nominal O.D. | | Approx. Weight | |
|------------------|-----|-------------------|-----------|------------------------------|-----|---------------|------------|----------------|-------|
| | | | | in | mm | in | mm | lbs/1k ft | kg/km |
| GPTM1602 | 16 | 2 | 26/30 | 0.030 | 0.8 | 0.182 x 0.300 | 4.6 x 7.6 | 35 | 52 |
| GPTM1603 | | 3 | 26/30 | 0.030 | 0.8 | 0.182 x 0.413 | 4.6 x 10.5 | 56 | 83 |
| GPTM1402 | 14 | 2 | 41/30 | 0.030 | 0.8 | 0.200 x 0.336 | 5.1 x 8.5 | 53 | 79 |
| GPTM1403 | | 3 | 41/30 | 0.030 | 0.8 | 0.200 x 0.467 | 5.1 x 11.9 | 77 | 115 |
| GPTM1202 | 12 | 2 | 65/30 | 0.030 | 0.8 | 0.219 x 0.374 | 5.6 x 9.5 | 72 | 107 |
| GPTM1203 | | 3 | 65/30 | 0.030 | 0.8 | 0.219 x 0.524 | 5.6 x 13.3 | 104 | 155 |
| GPTM1002 | 10 | 2 | 105/30 | 0.030 | 0.8 | 0.244 x 0.424 | 6.2 x 10.8 | 102 | 152 |
| GPTM1003 | | 3 | 105/30 | 0.030 | 0.8 | 0.245 x 0.610 | 6.2 x 15.5 | 150 | 223 |

Notes

- Soft-annealed, tinned copper conductor
- Polyvinyl chloride (PVC) insulation
- Polyvinyl chloride (PVC) jacket
- Class K stranding
- ABYC
- Coast Guard
- RoHS Compliant
- Standard jacket color: white

Applications

For use in marine applications. Rated for continuous use up to 75°C wet and 105°C dry.

| No. of Conductors | Standard Conductor Insulation Colors |
|-------------------|--------------------------------------|
| 2 | Black, White |
| 3 | Black, White, Green |