

Double Jacketed Buried Service Wire

Spec. 4287

WITH ALUMINUM SHIELD ICEA S-86-634

Product Construction:

Conductors:

- Solid annealed copper

Insulation:

- High density polyethylene

Pairing:

- Varying pair lays

Core Filling:

- 80°C filling and flooding compounds

Inner Jacket:

- Linear low density polyethylene

Shield:

- Polymer-coated 0.008" aluminum tape

Rip Cord:

- Under the outer jacket

Outer Jacket:

- Black, linear low density polyethylene

Application(s):

- Intended for use in buried service application to the subscriber loops

Compliances:

- ICEA S-86-634
- RoHS Compliant (effective 1/1/10)

Packaging:

- Non-returnable plywood reels in lengths as shown above



Nominal Cable Data

| CATALOG NUMBER | PAIRS AWG | | O.D. (INCHES) | WEIGHT (LBS/MFT) | STANDARD LENGTH (FT) |
|----------------|-----------|----|---------------|------------------|----------------------|
| 2095138 | 2 | 22 | 0.33 | 51 | 1000 |
| 2095125 | 2 | 22 | 0.33 | 51 | 2500 |
| 2095126 | 2 | 22 | 0.33 | 51 | 5000 |
| 2095146 | 3 | 22 | 0.35 | 62 | 1000 |
| 2095127 | 3 | 22 | 0.35 | 62 | 2500 |
| 2095128 | 3 | 22 | 0.35 | 62 | 5000 |
| 2095137 | 6 | 22 | 0.41 | 88 | 1000 |
| 2095129 | 6 | 22 | 0.41 | 88 | 2500 |
| 2095130 | 6 | 22 | 0.41 | 88 | 5000 |
| 2095131 | 2 | 24 | 0.30 | 42 | 2500 |
| 2095132 | 2 | 24 | 0.30 | 42 | 5000 |
| 2095133 | 3 | 24 | 0.32 | 54 | 2500 |
| 2095134 | 3 | 24 | 0.32 | 54 | 5000 |
| 2095135 | 6 | 24 | 0.33 | 68 | 2500 |
| 2095136 | 6 | 24 | 0.33 | 68 | 5000 |

Data subject to change without notice. Contact your Customer Service Representative for latest information.