


NOTICE TO ALL PERSONS RECEIVING THIS DRAWING
 THIS DRAWING IS ONLY CONDITIONALLY ISSUED AND REMAINS SUBJECT TO MODIFICATION OR CANCELLATION WITHOUT NOTICE. THE USER SHALL BE RESPONSIBLE FOR VERIFYING THE ACCURACY OF THE INFORMATION CONTAINED HEREIN. NO WARRANTY IS MADE BY THE DRAWING OR THE INFORMATION CONTAINED HEREIN. THE USER SHALL BE RESPONSIBLE FOR VERIFYING THE ACCURACY OF THE INFORMATION CONTAINED HEREIN. THE USER SHALL BE RESPONSIBLE FOR VERIFYING THE ACCURACY OF THE INFORMATION CONTAINED HEREIN.

ECR	REL. DATE	REV. LET.	REVISION	CHK. BY	APPROVED BY
	6/11/03	A	SEE DCBA 23593-055	WAC	ENG N.E. DA
	7/7/03	A	SEE DCBA 23593-055A	WAC	PC SM FGH
	3/30/07	B	SEE DCBA 23593-055C	RFP	PC SM EML
				RFP	RCG PC FSP

2X CONDUCTOR PER MIL-W-22759/33
 24 AWG 19 STRANDED SILVER
 COATED HIGH STRENGTH COPPER
 CROSS LINKED MODIFIED ETHE
 INSULATION
 COLOR 1X WHITE
 1X WHITE/BLUE
 (SOLID COLORS OR WHITE WITH
 COLORED STRIPES ARE ACCEPTABLE)
 OUTER JACKET, XLETFE



ROUND, SILVER
 COATED COPPER SHIELD

NOTES:

- CABLE TO MEET THE REQUIREMENTS OF M27500-24SC2523 FOR:
 A. CONDUCTOR CONSTRUCTION.
 B. CABLE JACKET INSULATION.
 C. SHIELD APPLICATION.
 D. ELECTRICAL REQUIREMENTS.
- MARKER TAPE IDENTIFICATION IS NOT REQUIRED IN THIS CABLE.

UNCONTROLLED COPY
 REVISION BEFORE USE

UNLESS OTHERWISE SPECIFIED	APPROVALS	DATE	REV.
CONDUCTOR SIZE	WAC	6/11/03	A
INSULATION	WAC	6/11/03	A
SHIELD	WAC	6/11/03	A
OUTER JACKET	WAC	6/11/03	A
MARKER TAPE	WAC	6/11/03	A
ALL DIMENSIONS	WAC	6/11/03	A
DO NOT SCALE DRAWING	WAC	6/11/03	A
NATURAL SPEC.	WAC	6/11/03	A
FRESH SPEC.	WAC	6/11/03	A

ORIGINATOR	WAC	6/11/03
DESIGNED	WAC	6/11/03
ENGINEER		
CHECKED		
DATE	6/11/03	
BY	WAC	
SCALE	AS SHOWN	
PREPARED UNDER CONTRACT		
FIGURE NO.		
SCALE	NONE	

LABORATORIES, INC.	23593-055
BRANFORD, CT 06405-0010	PART NUMBER
CABLE, ELECTRICAL,	
2 CONDUCTOR (M27500)	
FORMING NO.	
REV.	
B 00060	23593-055
SCALE	NONE
SHEET	1 OF 1