

NOTICE TO ALL PERSONS RECEIVING THIS DRAWING
 THIS DRAWING IS THE PROPERTY OF LABORATORIES, INC. AND IS LOANED TO YOU FOR YOUR INFORMATION ONLY. IT IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF LABORATORIES, INC. ANY UNAUTHORIZED REPRODUCTION OR TRANSMISSION OF THIS DRAWING IS PROHIBITED.

WARNING: EXPORT CONTROLLED
 THIS DOCUMENT CONTAINS TECHNICAL DATA WITHIN THE DEFINITION OF THE INTERNATIONAL TRAFFIC IN ARMS REGULATIONS AND IS SUBJECT TO THE EXPORT CONTROL LAWS OF THE U.S. GOVERNMENT. TRANSFER OF THIS DATA BY ANY MEANS TO A FOREIGN PERSON, WHETHER IN THE UNITED STATES OR ABROAD, WITHOUT AN EXPORT LICENSE OR OTHER APPROVAL FROM THE U.S. DEPARTMENT OF STATE, IS PROHIBITED.

DESCRIPTION:

MEDIUM WEIGHT, OIL AND FUEL RESISTANT, ECONOMY CONSTRUCTION AIRCRAFT CABLE, CONSTRUCTED TO WITHSTAND 600 V RMS AND 400°F CONTINUOUSLY

EXTRUDED CLEAR REP JACKET

36 GAUGE SILVER COATED COPPER WIRE BRAID

3X M22759/4-20-9 WHITE OR NATURAL (TAN)

Ø .223 MAX

NOTES:

- 1.) CABLE SHALL CONFORM TO M27500-20R14S05 EXCEPT THE SPECIFIED WIRE COLOR CODING AND PRINTED IDENTIFICATION ON WIRE AND CABLE ARE ACCEPTABLE BUT NOT REQUIRED.

ECR	REL DATE	REV. LET.	REVISION	REV. BY	CHK BY	APPROVED BY
	10-01-12	-	(DCRA 23593-102- - INITIAL RELEASE.	JAV	JAV	DE M.E. OE
						RCG SMA WDG

23593-102	6844565
PART NUMBER	CUSTOMER PIN
Laboratories, Inc.	
BRANFORD, CT 06405-0010	
TITLE	
CABLE, ELECT, SHIELDED & JACKETED, 3 COND	
REV B	REV
00060	23593-102
SCALE	SHEET 1 of 1

UNLESS OTHERWISE SPECIFIED:
 TOLERANCES ARE IN INCHES.
 DECIMALS: .010
 FRACTIONS: 1/32
 ANGLES: 3°
 ALL DIAMETERS: Ø .010
 BREAK EDGES: .005 R
 FILLS TO BE: JG .020
 SURFACE FINISH: 125

FINISH SPEC:

MATERIAL SPEC: