

TWIST-LOCK® Devices
2 Pole, 3 Wire Grounding
 30 Ampere, 125 and 250 Volts
VALISE® Plugs and Connector Bodies



HBL2611VY



HBL2613VY



HBL60CM31V



HBL60CM32V



Valise Plugs IP20 SUITABILITY

Description	Cord Dia.	Catalog Numbers	
Yellow nylon.	.590"-.930" (15.0-23.6)	HBL2611VY	HBL2621VY
Corrosion resistant, yellow nylon.	.590"-.930" (15.0-23.6)	HBL26CM11V	-
Black nylon.	.590"-.930" (15.0-23.6)	HBL2611VBK	HBL2621VBK



NEMA L5-30P
30A 125V
UL/CSA
2 HP



NEMA L6-30P
30A 250V
UL/CSA
2 HP



NEMA L5-30R
30A 125V
UL/CSA



NEMA L6-30R
30A 250V
UL/CSA

Valise Connector Bodies IP20 SUITABILITY

Description	Cord Dia.	Catalog Numbers	
Yellow nylon.	.590"-.930" (15.0-23.6)	HBL2613VY	HBL2623VY
Corrosion resistant, yellow nylon.	.590"-.930" (15.0-23.6)	HBL26CM13V	-
Black nylon.	.590"-.930" (15.0-23.6)	HBL2613VBK	HBL2623VBK

Notes: Connector bodies are not HP rated.
 HP ratings are AC only.
 See page B-88 for technical information.

Weatherproof Accessories IP55** SUITABILITY

Description	Catalog Numbers
Yellow Seal-Tite® elastomer triple seal cover for use with Valise plugs when used in cord set and Valise connector bodies when used with flanged inlet.	HBL60CM31V*
Yellow Seal-Tite elastomer triple seal cover for use with Valise connector bodies.	HBL60CM32V*

Note: **When installed and used properly with plug and connector body combinations.
 * Not UL Listed, CSA Certified.