

HDM250HIRC2



Article Number: 151-00437

Standard Torque Mount, Mounting Hole 0.25", Max Torque 115.0 lb - in, PA66HIRHS, Black, 100/pkg



Download spec sheet

Base Data

Local Order Number HDM250HIRC2

Type HDM25

Color Black (BK)

Features and Benefits

- Mount and tie combination makes it easy to service bundles in the field.
- Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.
- Eliminates the needs for multiple sized fix diameter clamps.

Product Description This mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.

Fixation Method (FF) Screw Mounting and Rivet

Short Description Standard Torque Mount, Mounting Hole 0.25", Max Torque 115.0 lb - in, PA66HIRHS, Black, 100/pkg

Product Dimensions

Length L (Imperial) 1.4 "

Length L (Metric) 35.8 mm

Width W (Imperial) 0.75 "

Width W (Metric) 19.0 mm

Cable Tie Width Max. (Imperial) 0.5 "

Cable Tie Width Max. (Metric) 12.7 mm

Width W2 (Imperial) 0.52 "

Width W2 (Metric) 13.3 mm

Height H (Imperial) 0.66 "

Height H (Metric) 16.7 mm

Height H2 (Imperial) 0.31 "

Height H2 (Metric) 8.0 mm

Mounting Hole Diameter D (Imperial) 0.25 "

Mounting Hole Diameter D (Metric) 6.2 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100 Pieces

Carton Quantity 2500

Material and Specifications

Material Polyamide 6.6 high impact modified (PA66HIR)

Material Shortcut PA66HIRHSUV
Flammability UL94 HB
Maximum Torque (lbf-ft) 9.583 lbf-ft
Maximum Torque (kgf-cm) 132.5 kgf-cm
Operating Temperature -40°F to +230°F (-40°C to +110°C)
ROHS compliant (Article 4 - 1) Yes