

## HDM320BHIHSUVC2



Article Number: 151-00444

High Torque Mount, Mounting Hole .3125", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg



Download drawing



Download spec sheet

### Base Data

**Local Order Number** HDM320BHIHSUVC2

**Type** HDM320

**Color** Black (BK)

- Features and Benefits**
- Mount and tie combination makes it easy to service bundles in the field.
  - Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.
  - Eliminates the needs for multiple sized fix diameter clamps.

**Product Description** This heavy duty mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.

**Fixation Method (FF)** Screw Mounting and Rivet

**Short Description** High Torque Mount, Mounting Hole .3125", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg

### Product Dimensions

**Length L (Imperial)** 1.9 "

**Length L (Metric)** 47.0 mm

**Width W (Imperial)** 1.0 "

**Width W (Metric)** 25.0 mm

**Cable Tie Width Max. (Imperial)** 0.5 "

**Cable Tie Width Max. (Metric)** 12.7 mm

**Mounting Hole Diameter D (Imperial)** 0.4 "

**Mounting Hole Diameter D (Metric)** 8.31 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 100

**Carton Quantity** 500

**Weight (Metric)** 19.3 kg

### Material and Specifications

**Material** Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

**Material Shortcut** PA66HIRHSUV

**Flammability** UL94 V2

**Maximum Torque (lbf-ft)** 114 lbf-ft

**Maximum Torque (kgf-cm)** 1576 kgf-cm

**Operating Temperature** -40°F to +230°F (-40°C to +110°C)

ROHS compliant (Article 4 - 1) Yes

---

© HellemannTyton 2015