



**Prestolink SAE J156**  
**Automotive Fuselink Cable**  
150°C

**Features**

Conductors available in tinned or copper  
Insulation: 150°C XLPO  
RoHS and REACH Compliant

**Product Design Options**

Custom strand constructions  
Custom diameter to meet design criteria  
Various colors  
Packaging options: reels

**Applications**

Cables used for automotive electrical

<b>AWG size</b>	<b>Number of Strands</b>	<b>Strand Size (ga)</b>	<b>Nom Cond OD (in)</b>	<b>Nom OD (in)</b>	<b>Nom Wall (in)</b>	<b>Approx. Net Weight (lbs/mft)</b>	<b>Approx. Cu (lbs/mft)</b>
20	7	28	0.038	0.116	0.037	10	3
18	16	30	0.048	0.127	0.037	122	5
16	19	29	0.057	0.139	0.041	160	8
14	19	27	0.071	0.155	0.041	217	12
12	19	25	0.089	0.184	0.046	324	18
10	19	23	0.108	0.213	0.046	472	30
8	19	21	0.137	0.258	0.056	720	48
6	37	21	0.190	0.321	0.062	127	92

**Customer Service Group**

1 Prestolite Drive Paragould, Arkansas 72450  
Phone: 800-952-3842 870-236-8141  
Fax: 870-239-6139  
Web: [www.prestolitewire.com](http://www.prestolitewire.com)