

157-00164



Article Number: 157-00164

Description: 1-Piece Cable Tie/Fir Tree Mount With Disc, 25mm Offset/90° Angle, 9.3"L, 6.1–7mm Hole, PA66HIRHS, Bk, 500/pkg

Base Data	
Local Order Number	157-00164
Type	T50ROSFT6SO25R
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> • 25mm offset cable tie allows for the wire harness to be routed offset from the mounting surface with a cable tie solution versus bundling clips which have the ability to flex. • Offset bar creates additional strength with it's robust design to minimize potential flexing and shifting of the harness. • 90 Degree design allows for the bundle to sit securely underneath the offset bar and fir tree.
Quantity Per	box
Product Description	HellermannTyton's 90 Degree Offset Cable tie offers a robust alternative to bundling clips, when needing to route a harness offset from the mounting surface. This fir tree cable tie lends itself to various panel thicknesses within the automotive industry.
Short Description	1-Piece Cable Tie/Fir Tree Mount With Disc, 25mm Offset/90° Angle, 9.3"L, 6.1–7mm Hole, PA66HIRHS, Bk, 500/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	222N
Length L (Imperial)	9.3"
Length L (Metric)	237.7mm
Identification Plate Position	none
Length L2 (Metric)	25.0mm
Releasable Closure	No
Width W (Imperial)	0.201"
Width W (Metric)	5.1mm
Height H (Imperial)	.60"
Height H (Metric)	15.10mm
Bundle Diameter Min. (Imperial)	0.06"
Bundle Diameter Min. (Metric)	1.6mm

157-00164



Product Dimensions	Bundle Diameter Max. (Imperial)	1.97"
	Bundle Diameter Max. (Metric)	50.0mm
	Disc Diameter (Metric)	19.0mm
	Panel Thickness Max. (Imperial)	0.26"
	Panel Thickness Max. (Metric)	8.25mm
	Panel Thickness Min. (Imperial)	0.02"
	Panel Thickness Min. (Metric)	0.6mm
	Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm
	Mounting Hole Diameter D Min. (Imperial)	0.24"
	Mounting Hole Diameter D Max. (Imperial)	0.27"
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Material Cable Tie	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces