

Specification Sheet

Part Number: 157-00195



Offset Fir Tree Cable Tie, 25 mm, FT6, 8" Tie, 50lb Tensile Strength, PA66HIRHS, Black, 500/pkg

Article Number

157-00195

Type

T50ROSFT625SO

Color

Black (BK)

Features & Benefits

- One-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, through the design of the fir tree by ensuring positive and secure fixing into panels with thicknesses from 0.6-6.65mm.
- The offset on the cable tie creates an alternate solution when an offset fixing option is required and a tape clip cannot be used due to the design which reduces the potential of the bundle flexing or shifting.
- The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Quantity Per

carton

Product Description

HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description

Offset Fir Tree Cable Tie, 25 mm, FT6, 8" Tie, 50lb Tensile Strength, PA66HIRHS, Black, 500/pkg

Global Part Name

T50ROSFT625SO-PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

220.0

Length L (Imperial)

9.7

Length L (Metric)

247.2

Offset Length(Imperial)

0.98

Offset Length(Metric)

25.0

Fixation Method

Fir Tree

Identification Plate Position

none

Releasable Closure

No

Width W (Imperial)

0.20

Width W (Metric)

5.1

Bundle Diameter Min (Imperial)

0.08

Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Thickness T (Metric)	1.5
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.32
Panel Thickness Min (Metric)	0.50
Panel Thickness Max (Metric)	6.65
Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27
Mounting Hole Diameter D Max (Metric)	6.9
Disc Diameter(Metric)	19.0
Disc Diameter (Imperial)	0.75
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Material Cable Tie Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Operating Temperature (Metric) -40°F to +230°F (-40°C to +110°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909987

Content Unit(BMEcat) pcs.