


Specification Sheet

Part Number: T50LDH0M4



Article Number

117-05401

Type

T50LDH

Color

Black (BK)

Features & Benefits

- The tie contains a dual locking design to secure two bundles at once.
- Head design can also provide spacing between parallel bundles.
- Bent tail allows for quick insertion into head.

Quantity Per

bag

Product Description

The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description

Double-Head Cable Tie, 15.6" Long, 50lb Tensile Strength, PA66, Black, 1000/pkg

Global Part Name

T50LDH-PA66-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225.0

Length L (Imperial)

15.6

Length L (Metric)

395.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.19

Width W (Metric)

4.7

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.6

Bundle Diameter Max (Imperial)

2.0

Bundle Diameter Max (Metric)

100.0

Bundle Diameter 1st Loop Max (Imperial)

4.0

Bundle Diameter 1st Loop Max (Metric)

101.6

Bundle Diameter 2nd Loop Max (Imperial)

2.0

Bundle Diameter 2nd Loop Max (Metric)

50.8

Thickness T (Metric)

1.4

Material

Polyamide 6.6 (PA66)

Material Shortcut

PA66

Flammability

UL 94 V2

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +185°F (-40°C to +85°C)

ROHS Complaint

Yes

Certification/Specification WEB

UL-ZODZ2.E64139

UL Recognized (US)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

1000

Package Quantity (Metric)

1000

Customs Number

3926909987

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)