ALPHA WIRE COMPANY CUSTOMER PRODUCT SPECIFICATION

Part Number: 390645 Issue: 3

Page 1 of 1 Pages Issue Date: 2/16/2009 Effective Date: 2/16/2009

A. Construction <u>Diameters (In)</u>

I) Component 1 1 X 1 HOOKUP

a) Conductor 6 (133(7x19)/27) AWG TC

b) Insulation 0.045" Wall, Nom. Silicone Rubber 0.303+/- 0.004

(1) Print (D) 390645 15KVDC 0.045 WALL 6 AWG

(2) Color(s) WHITE, BLACK, RED

B. Industry Approvals

1) EU Directive 2002/95/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.

C. Physical & Mechanical Properties

Temperature Range
Bend Radius
Pull Tension
40 to 150°C
10X Cable Diameter
211 Lbs. Maximum

D. Electrical Properties (For Engineering purposes only)

1) Voltage Rating 15000 V_{DC}

2) Inductance 0.04 µH/ft, Nominal

3) Conductor DCR 0.43 Ω/1000ft @20°C, Nominal

E. Other

1) Packaging

- a) 1000 FT
- b) 500 FT
- c) 100 FT
- d) Bulk(Made-to-order)

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.