



Hueson Wire & Cable

Technical Data Sheet

Customer: IEWC Global Solutions

Quote Number: HWC-22-822

Date: 3/8/2024

Sales ID: Dylan Parent

Description: 19/C 16 26/30 TC SR-PVC/PVC

BUILD: **OD:**

Conductor: 16 AWG 26/30 Tinned Copper 0.060

Insulation: 0.015 " Semi-Rigid PVC 0.090

Color Code: Black, White, Red, Green, Orange, Blue, White/Black, Red/Black, Green/Black, Orange/Black, Blue/Black, Black/White, Red/White, Green/White, Blue/White, Black/Red, White/Red, Orange/Red, Blue/Red

Cable Assem: Bunch / Cable the 19 conductors 0.454

Tape: CMT 0.458

Tape Note: Clear Mylar Tape

Filler Note: Fibrillated polypropylene filler(s) for roundness as needed

Jacket Spec: 0.049 " PVC CMG FT-4

Jacket Color: Gray **Jacket Set-up:** Pressure Extruded **OD Tolerance:** +/- 0.010 0.551

Aesthetics: Cable May Have Convolutions

Print: E174416 (RU) AWM 2586 105C 600V 16 AWG --- LL109360 TYPE CMG 60C FT4

Packaging: Spool Part: SW-30-2 (30x14x10) Spool Description: Wood Put-up: 1000

UL Ratings: UL: 2586 105 Celsius 600 Volts

Additional Notes:

Ripcord under jacket


Black Inkjet Print

Environmental Compliance:

RoHS EU Directive 2011/65/EU (1, 2, and 3)

REACH Regulation 223

California Prop 65:

 This product may contain chemicals known to the state of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Customer Signature: _____