

Hueson Wire & Cable Technical Data Sheet

Customer:	IEWC	Global	Solutions
-----------	-------------	--------	------------------

Description: 6/C 20 7/28 TC PVC/PVC

BUILD: OD:

Conductor: 20 AWG 7/28 Tinned Copper 0.038

Insulation: 0.016 " 0.070

Color Code: Black, Red, White, Green, Orange, Blue

Cable Assem: Bunch / Cable the 6 conductors 0.214

Tape: NW 0.216

Tape Note: Over Cable Core

Filler Note: Fibrillated polypropylene filler for roundness

Jacket Spec: 0.020 "

Jacket Color: Gray Jacket Set-up: Pressure Extruded OD Tolerance: +/ 0.010 0.254

Aesthetics: Finished Cable Must be Round and Smooth

Print: E194074 20 AWG (UL) TYPE CM 75C OR AWM 2509 80C 300V --- C(UL) TYPE CMG FT4 ROHS

Packaging: Spool Part: RH-20-1 (20x12x8) Spool Description: Wood Put-up: 2500

UL Ratings: UL:

Additional Notes:

Print to be Ink Jet in Black Ink

Enviromental Compliance:

RoHS EU Directive 2011/65/EU (1, 2, and 3)

REACH Regulation 219

California Prop 65:

 \wedge

Customer Signature: