



Hueson Wire & Cable

Technical Data Sheet

Customer: IEWC Global Solutions

Quote Number: HWC-24-2490

Date: 6/21/2024

Sales ID: Brian Fleming

Description: 2/C 22 AWG 7/30 TC Unshielded mPPE/mPPE Black

BUILD:		OD:
Conductor: 22 AWG 7/30 Tinned Copper		0.030
Insulation: 0.009 " mPPE		0.048
<hr/>		
Color Code: 1) Black, 2) Red.		
<hr/>		
Cable Assem: Bunch / Cable the 2 conductors with 1.25" LHL.		0.096

Jacket Spec: 0.038 " mPPE			
Jacket Color: Black	Jacket Set-up: Pressure Extruded	OD Tolerance: +/- 0.010	0.172
Aesthetics: Finished Cable Must be Round and Smooth			

Print: RU AWM 21819 105C 600V VW-1

Packaging: Spool Part: ALP-P18-14-8 (18x14x8) Spool Description: Plastic Put-up: 5000

UL Ratings: UL: 21819 105 Celsius 600 Volts AWM Single Style 11028

Additional Notes:

Hueson Internal P/N: C6360 Black

Environmental Compliance:

RoHS EU Directive 2011/65/EU (1, 2, and 3)

REACH Regulation 223

California Prop 65:



This product may contain chemicals known to the state of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Customer Signature: _____