



Hueson Wire & Cable

Technical Data Sheet

Customer: IEWC Global Solutions

Quote Number: HWC-24-2526

Date: 7/2/2024

Sales ID: Brian Fleming

Description: 8/C 18 AWG 16/30 TC Unshielded PVC/PVC Black

BUILD: **OD:**

Conductor: 18 AWG 16/30 Tinned Copper 0.047

Insulation: 0.015 " Premium Grade PVC 0.077

Color Code: 1) Red, 2) Black, 3) Blue, 4) Green, 5) White, 6) Gray, 7) Brown, 8) Orange.

Cable Assem: Bunch / Cable the 8 conductors with 3.75" LHL. 0.259

Tape: NW 0.261

Filler Note: Fibrillated polypropylene or solid filler(s) for roundness.

Jacket Spec: 0.036 " Flexible PVC, Oil, Moisture UV Resistant, VW-1

Jacket Color: Black **Jacket Set-up:** Pressure Extruded **OD Tolerance:** +/- 0.010 0.331

Aesthetics: Cable May Have Convolutions

Print: No Print.

Packaging: Spool Part: ALP-P18-14-8 (18x14x8) **Spool Description:** Plastic **Put-up:** 1250

UL Ratings: UL: No UL

Environmental Compliance:

RoHS EU Directive 2011/65/EU (1, 2, and 3)

REACH Regulation 223

California Prop 65:



This product may contain chemicals known to the state of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Customer Signature: _____