



# Hueson Wire & Cable

## Technical Data Sheet

**Customer:** IEWC Global Solutions

**Quote Number:** HWC-24-2783

**Date:** 8/22/2024

**Sales ID:** Brian Fleming

**Description:** 4/C 18 AWG 41/34 TC-SB Unshielded PVC/PVC Black

**BUILD:** **OD:**

**Conductor:** 18 AWG 41/34 Tinned Copper Smoothbunch 0.045

**Insulation:** 0.010 " Premium Grade PVC 0.065

**Color Code:** 1) White, 2) Black, 3) Red, 4) Green.

**Cable Assem:** Bunch / Cable the 4 conductors. 0.161

**Tape:** NW 0.163

**Tape Note:** Pull in Non-Woven Tape. 25% Overlap Minimum.

**Filler Note:** Fibrillated polypropylene filler(s) for roundness.

**Jacket Spec:** 0.032 " 70A PVC

**Jacket Color:** Black **Jacket Set-up:** Pressure Extruded **OD Tolerance:** +/- 0.010 0.225

**Aesthetics:** Cable May Have Convolutions

**Print:** No Print.

**Packaging:** Spool Part: ALP-P12-10-5 ERROR Spool Description: 12x10x5 PI Put-up: 1000

**UL Ratings:** UL: No UL

**Enviromental Compliance:**

RoHS EU Directive 2011/65/EU (1, 2, and 3)

REACH Regulation 223

California Prop 65:



This product may contain chemicals known to the state of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Customer Signature:** \_\_\_\_\_