

For more Information  
please call

1-800-Belden1



### General Description:

CSPE - Chlorosulphonated Polyethylene insulation has excellent heat resistance, color stability and electrical properties and is recommended for motor leads for Class 130(B) insulation systems.

### Physical Characteristics (Overall)

#### Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 1            | 18  | 16x30     | TC - Tinned Copper |

Total Number of Conductors: 1

#### Insulation

Insulation Material:

| Insulation Material                   | Wall Thickness (mm) |
|---------------------------------------|---------------------|
| CSPE - Chlorosulphonated Polyethylene | 0.762               |

#### Overall Insulation

#### Overall Cable

Overall Nominal Diameter: 2.794 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

|                                       |                  |
|---------------------------------------|------------------|
| UL AWM Style:                         | 3190             |
| UL Rating:                            | 300 V RMS, 105°C |
| CSA Rating:                           | 300 V RMS, 105°C |
| CSA Type:                             | CL1052           |
| EU Directive 2011/65/EU (ROHS II):    | Yes              |
| EU Directive 2000/53/EC (ELV):        | Yes              |
| EU Directive 2002/95/EC (RoHS):       | Yes              |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004       |
| EU Directive 2002/96/EC (WEEE):       | Yes              |
| EU Directive 2003/11/EC (BFR):        | Yes              |
| CA Prop 65 (CJ for Wire & Cable):     | Yes              |
| MII Order #39 (China RoHS):           | Yes              |

#### Plenum/Non-Plenum

Plenum (Y/N): No

### Put Ups and Colors:

| Item #        | Putup    | Ship Weight | Color | Notes   | Item Desc              |
|---------------|----------|-------------|-------|---------|------------------------|
| 34918 002500  | 500 FT   | 6.000 LB    | RED   | F       | #18 STR CSPE 105C 300V |
| 34918 0025000 | 5,000 FT | 55.000 LB   | RED   | C I U Z | #18 STR CSPE 105C 300V |
| 34918 010500  | 500 FT   | 5.500 LB    | BLACK | F       | #18 STR CSPE 105C 300V |
| 34918 0105000 | 5,000 FT | 55.000 LB   | BLACK | C I U Z | #18 STR CSPE 105C 300V |

#### Notes:

C = CRATE REEL PUT-UP.

F = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'

I = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'

U = TOPCOAT ADDERS ON STOCK SOLID COLORS. MINIMUM ORDER 10000' PER COLORCOMBINATION. (SEE TOPCOAT ADDER TABLE)

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1    Revision Date: 01-11-2011

© 2015 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.