

# Braidless Silicone Rubber

150° C 600 Volts

## Ratings/Approvals

UL Style 3212, 3213, 3214

## Construction

Stranded tin plated copper conductor

Extruded Silicone Rubber

Standard color coding - available in solid colors or stripes

\*Where totally enclosed: reduced wall thickness available for 24 to 12awg UL Style 3529, 3133, 3134 and 3530

AWG (Stranding)	Mils/OD	Weight/mft	UL Style	CSA
24 (7)	45/.114"	7	3212	AWM IA FT2
22 (7)	45/.120"	8	3212	AWM IA FT2
20 (7)	45/.128"	10	3212	AWM IA FT2
18 (16)	45/.135"	12	3212	AWM IA FT2
16 (26)	45/.147"	16	3212	AWM IA FT2
14 (41)	45/.162"	22	3212	AWM IA FT2
12 (65)	45/.177"	31	3212	AWM IA FT2
10 (105)	45/.204"	45	3212	AWM IA FT2
8 (133)	60/.285"	79	3213	AWM IA FT2
6 (133)	60/.326"	114	3213	AWM IA FT1
4 (133)	60/.380"	167	3213	AWM IA FT1
2 (259)	60/.449"	260	3213	AWM IA FT1
1 (259)	60/.532"	333	3214	AWM IA FT1
1/0 (259)	80/.570"	415	3214	AWM IA FT1
2/0 (259)	80/.625"	494	3214	AWM IA FT1
3/0 (259)	80/.675"	626	3214	AWM IA FT1
4/0 (259)	80/.746"	759	3214	AWM IA FT1

Consult factory for alternate conductor and stranding options.