

Braided Silicone Rubber

200° C 300/600Volts

Ratings/Approvals

300 Volts - UL Style 3122 SF-1

600 Volts - UL Style 3071, 3074, 3075, 3231 SF-2

Construction

Stranded tin or nickel plated copper conductor

Extruded Silicone Rubber

Treated Braided Fiberglass

Standard color coding - available in color or stripes

300 Volt				
AWG (Stranding)	OD	Weight/mft	UL	CSA
22(7)	.074"	4	3122	SEWF-1/AWM I A/B
20(7)	.081"	6	3122	SEWF-1/AWM I A/B
18(7)	.096"	8	3122/SF-1	SEW-1/AWM I A/B
16(7)	.103"	12	3122	SEW-1/AWM I A/B

600 Volt				
AWG (Stranding)	OD	Weight/mft	UL	CSA
24(7)	.099"	6	3231	AWM I A/B
22(7)	.104"	7	3231	SEWF-2/AWM I A/B
20(7)	.111"	8	3231	SEWF-2/AWM I A/B
18(7)	.121"	11	3231/3071/SF-2	SEW-2/AWM I A/B
16(7)	.133"	15	3231/3071/SF-2	SEW-2/AWM I A/B
14(7)	.146"	21	3231/3071/SF-2	SEW-2/AWM I A/B
12(19)	.163"	30	3231/3074/SF-2	SEW-2/AWM I A/B
10(19)	.218"	50	3231/3075/SF-2	SEW-2/AWM I A/B
8(19)	.286"	82	3231	SEW-2/AWM I A/B
6(19)	.326"	119	3231	SEW-2/AWM I A/B
4(133)	.406"	182	3231	SEW-2/AWM I A/B
2(259)	.474"	275	3231	SEW-2/AWM I A/B
1(259)	.557"	353	3231	SEW-2/AWM I A/B
1/0(259)	.595"	436	3231	SEW-2/AWM I A/B
2/0(259)	.685"	535	3231	SEW-2/AWM I A/B
3/0(259)	.735"	669	3231	SEW-2/AWM I A/B
4/0(259)	.806"	804	3231	SEW-2/AWM I A/B

Consult factory for alternate conductor and stranding options.