

Polyester braided sleeving, expansion rate: 3:1, **UL94V0** classification

Helagaine HEGPV0X

Helagaine HEGPVOX is especially suitable for areas wherever fire protection is important as well as a higher expansion ratio of the braided sleeve. Helagaine HEGPV0X offers superior cable protection for machine tools, robotics and automatic equipment. Helagaine HEGPVOX had been successfully tested to DIN5510-2 and NF F 16-101 and can thus be used in many railway applications.

Features and Benefits

- Made of sturdy polyester
- Self-extinguishing according to UL94 V0 for enhanced fire protection
- Highly flexible
- Expansion ratio of 3:1
- Easy to apply over irregular shapes
- Good abrasion resistance



Helagaine HEGPV0X braided sleeving.

MATERIAL	Polyester (PBT)	
Operating Temperature	are -50 °C to +150 °C, intermittent +200 °C	
Melting Point	+225 °C	
Flammability	UL94 V0, FMVSS 302	
Specifications	NF F 16-101, UL-Recognised	

cut with the hot cutting

RoHS

To prevent fraying, the sleeve can be cut with the hot cutting
can be cut with the hot cutting
tool HSG0. See page 533.

ТҮРЕ	Bundle Ø min.	Bundle Ø max.	Colour	Reel Length	Article-No.
HEGPV0X03	2.0	6.0	Black with White Identification Yarn (BKIDWH)	200 m	170-50030
HEGPV0X06	3.0	10.0	Black with White Identification Yarn (BKIDWH)	200 m	170-50060
HEGPV0X09	5.0	16.0	Black with White Identification Yarn (BKIDWH)	100 m	170-50090
HEGPV0X12	6.0	19.0	Black with White Identification Yarn (BKIDWH)	100 m	170-50120
HEGPV0X20	12.0	32.0	Black with White Identification Yarn (BKIDWH)	100 m	170-50200
HEGPV0X30	19.0	45.0	Black with White Identification Yarn (BKIDWH)	50 m	170-50300
HEGPV0X40	32.0	70.0	Black with White Identification Yarn (BKIDWH)	50 m	170-50400
HEGPV0X50	38.0	76.0	Black with White Identification Yarn (BKIDWH)	50 m	170-50500

All dimensions in mm. Subject to technical changes.

Colour grey available on request. Cuts in any lengths. Minimum Order Quantity (MOQ) may differ from package content.

