



[www.iewc.com](http://www.iewc.com)

Issue Date: 2/23/2023

Issue: 1

**Construction**

<b>Description:</b> 5/C 22 19/34 BC PVC/PVC		<b>Diam. (In)</b>
<b>Component:</b>	5 Conductors	
<b>Conductor:</b>	22 AWG 19/34 Bare Copper to ASTM B-174	0.034 "
<b>Insulation:</b>	0.013" Premium Grade PVC	0.060 "
<b>Color Code:</b>	Red, Blue, Green, White, Black	0.060 "
<b>Cable Assembly:</b>	Bunch Cable 5 Conductors	0.161 "
<b>Fillers</b>	Fibrillated polypropylene fillers for roundness (optional)	0.161 "
<b>Separator:</b>	Non Woven Polyester	0.165 "
<b>Jacket:</b>	0.031" Flexible PVC, Oil, Moisture UV Resistant, VW-1	0.227 "
<b>Jacket Color:</b>	White Pressure Extruded 0.227 +/- 0.010"	0.227 "
<b>Put-ups:</b>	5,000FT Preferred Spool Size: 24" x 12" Wood	
<b>Print:</b>	E477982 UH RU AWM 20811 105C 600V OR 2661 105C 300V VW-1--- cRU AWM I/II A	
<b>Indent</b>	105C 600V FT-1	

<b>Specifications:</b>	<u>AWM</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>
<b>UL</b>	AWM 2661	105C	300	VW-1
	AWM 20811	105C	600	VW-1
<b>Canadian cRU</b>	AWM	105C	300	FT-1 I/II A/B

**Designed for UL Standard 1598 Clause 6.9.3 AWM Cables for use in the USA**

**Environmental Compliance**

- RoHS EU Directive 2011/65/EU (1&2&3)
- REACH Regulation 210:
- California Prop 65:



This product may contain chemicals known to the state of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)