

CONSTRUCTIONS

- + Fine Tinned/Bare Copper Strand to ASTM Standards
- + Available in all Insulations
- + Multi-Conductor Cables
- + Also available in Military Grade & Non-Halogen Eco-Friendly
- + High Flex

UNBEATABLE PROTECTION FROM

- + Weather and Heat
- + Oil and Solvents
- + Pinch and Abrasion
- + Hydrolysis
- + Low Temperature Flexing
- + Salt/Fresh Water Immersion
- + Raw Sewage
- + ASTM Fuels and Oils
- + Flame/Ignition
- + Fungus

Available in the smallest diameter 600 Volt and 1000 Volt TPU cables allowable by UL

APPLICATION USE

- + Transportation
- + Agriculture
- + Outdoor Lighting
- + Industrial
- + Down Hole Drilling
- + Ocean/Marine
- + Continuous Flex

Learn more.
Scan with your smartphone.



TPU CABLE

When your application requires **the ultimate protection from environmental damage**, you can count on Hueson TPU (Thermoplastic Polyurethane) cable.

AWM Style #	Min (mils)	Cond (min)	Temp (°C)	Volts	Flame
10771	30	32 AWG	80	600	Horizontal
20233	30	36 AWG	80	300	Cable
20234	45	36 AWG	80	1000	Cable
20235	45	36 AWG	80	N/A	Cable
20236	30	36 AWG	80	30	Cable
20375	30	36 AWG	105	300	Cable
20668	30	36 AWG	90	300	Cable
20669	45	40 AWG	90	600	Horizontal, Cable
20952	45	36 AWG	105	600	Cable
21209	30	40 AWG	90	1000	Cable
21753	30	50 AWG	90	300	Cable
21754	30	50 AWG	90	300	Horizontal
21755	30	50 AWG	90	600	Cable
21756	30	50 AWG	90	600	Horizontal
21757	30	50 AWG	90	1000	Cable
21758	30	50 AWG	90	1000	Horizontal
21765	30	50 AWG	105	300	Cable
21766	30	50 AWG	105	300	Horizontal
21767	30	50 AWG	105	600	Cable
21768	30	50 AWG	105	600	Horizontal
21769	30	50 AWG	105	1000	Cable
21770	30	50 AWG	105	1000	Horizontal
21781	30	50 AWG	90	300	Horizontal
21782	30	50 AWG	90	600	Horizontal



Hueson Corporation

38 Sutton Street | Northbridge, MA 01534
p 508-234-6372 | f 508-234-0274
info@huesonwire.com | huesonwire.com