



PRODUCT INFORMATION SHEET

FUSIBLE LINK WIRE

150°C - Heavy Duty Thermoset Elastomer Insulated (HDT) - Cross Linked Polyolefin Insulated

Features

Copper Conductors per ASTM B3 (Bare Copper) & ASTM B33 (Tinned Copper)
Insulation Material: Crosslinked Polyolefin
RoHS Compliant

Applications

Low tension cables for -40°C to 150°C
Low voltage ≤ 60 V DC
Temperature -40°C to 150°C

Compliance

SAE: J1128 HTS
SAE: J156

Product Options

Colors available upon request
Packaging Options: Drums and Reels, various sizes and disposal or recyclable

Conductor Size	Number of Strands	Conductor Area, Minimum	Insulation Thickness, Nominal	Insulation Thickness, Minimum	Cable OD, Maximum
ga	#	cmils	mm	mm	mm
20	19	1 072	0.91	0.64	3.10
18	16	1 537	0.94	0.66	3.40
16	19	2 336	1.02	0.71	3.70
14	19	3 702	1.04	0.73	4.20
12	19	5 833	1.17	0.82	5.10
10	19	9 343	1.17	0.82	5.70
8	19	14 810	1.40	0.98	7.00
6	37	24 538	1.09	0.76	7.8

Rev 0 (2022-10-28)

Written by: TCunningham