



Hueson Wire
 134 Ferry St.
 South Grafton, Ma 01560
 www.huesonwire.com

Issue Date: 12/2/22

Issue: 1

Construction

Description: 9/C Composite 2/C 14 19 BC XLP+ 6/C 16 19 BC+ 1/C 10 105BC XLP/PVC			Diam. (In)
Components:	9 Conductors		
Conductor #1:	14 AWG 19/27 Bare Copper	2 Conductors	
Insulation:	0.016" XLPE to SAE J-1128		0.103 "
Color Code:	Red + Red/Black		
Conductor #2:	16 AWG 19/.0117" Bare Copper	6 Conductors	
Insulation:	0.016" XLPE to SAE J-1128		0.0885
Color Code:	Blue, Blue/Black, Yellow, Yellow/Black, Orange, White		
Conductor #3:	10 AWG 105/30 Bare Copper	1 Conductors	
Color Code:	Black		0.158 "
Cable Assembly:	Bunch Cable 9 Conductors		
Fillers	Fibrillated polypropylene as needed for roundness		
Separator:	Non-Woven Polyester Wrapping		
Jacket:	0.039 Flexible PVC, Oil, Moisture UV , VW-1	0.445 +/- .010"	0.445
Jacket Color:	Black		0.445
Put-ups:	TBD	Preferred Spool Size: TBD	
Print:	10 AWG 1C + 14 AWG 2C + 16 AWG 6C INNER CONDS 125C XLPE PER SAE J1128 AND OUTER JACKET IS 105C PVC-MEETS REQUIREMENTS OF THE UL1581 UV/SUNLIGHT RESISTANCE TEST - MADE IN USA (Month/Year) (Seq. FT) ROHS-2		

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2&3)
- REACH Regulation 210:
- California Prop 65:

IQ-22018



This product may contain chemicals known to the state of California to cause cancer. For more information go to www.P65Warnings.ca.gov