



Issue Date: 9/22/2015

Issue: 1

Construction

Description:	2/C 14 (41) PVC/PVC	Diam. (In)
Component:	2 Conductors	
Conductor:	14 AWG 41/30 Tinned Copper to ASTM B-174	0.075"
Insulation:	0.03"	0.135"
Color Code:	Black, and Red	0.135"
Cable Assembly:	2 Conductors Bunched Cabled	0.27"
Fillers	Fibrillated polypropylene for roundness	0.27"
Tape:	Non-Woven or Clear Mylar Separator Tape for Strip-Ability (optional)	0.273"
Jacket:	0.032" AWM Jacket Compound	0.337"
Jacket Color:	White	0.337"

Print: E174416 RU AWM 2661 105°C 300V VW-1 cUR I/II A 105° C 300V FT1

Indent

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>	<u>UL List</u>
UL	AWM-2661	105°C	300	VW-1	
Canadian cRU	AWM	105°C	300	FT-1	

Environmental Compliance

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65:



Issue Date: 9/22/2015
Issue: 1

Drawing/Rotation:

