



PRODUCT DATA SHEET

Controlled Document - Engineering Drive


1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 720015
DESCRIPTION: 20/2 SHIELDED LOW CAP CABLE
CONSTRUCTION: This cable consists of two bare copper insulated conductors with an overall shield+drain and a Jacket
APPROVALS: None

Construction Parameters:

Cable Cross-Section

Conductor	20 AWG Bare Copper
Stranding	7/28
Insulation Material	Foamed Polyethylene
Insulation Thickness	0.032" Nom.
Insulated Conductor Diameter	0.100" Nom.
Number of Conductors	2
Lay Length	3.00" Nom.
Shield	Alum/Mylar (Al. side out)
Drain	20 AWG (7/28) Stranded Tinned Copper
Jacket Material	PVC
Jacket Thickness	0.022" Nom.
Overall Cable Diameter	0.248" Nom.
Approximate Cable Weight	28.0 Lbs/1M' Nom.



Electrical Properties:

Temperature Rating	90C Insulation, 105C Jacket		
Operating Voltage	300 V RMS Max.		
	<u>Minimum</u>	<u>Nominal</u>	<u>Maximum</u>
Capacitance Between Conductors @ 1 KHz	10.9 pF/ft Nom.	11.0 pF/ft Nom.	12.1 pF/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	21.1 pF/ft Nom.	23.5 pF/ft Nom.	25.8 pF/ft Nom.
DC Resistance per Conductor @ 20°C	9.27 Ohms/1M' Nom.		
Characteristic Impedance	110 Ohms Nom.		

Insulation Colors	Yellow Green
Jacket Color	Gray
Legend (Black Surface Ink Print)	J-1939 TYPE-MULTIPLEX

This product complies with European Directive 2011/65/EU (RoHS-2)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____

Customer Approval _____

Specification Issue Date: March 6, 2013