



Description: Three Conductors, 18 AWG
 Overall Braid Shield
 and PVC Jacket

Date: 5/21/2009

JM Part Number: JM55782

Reference: TBD

Components Three 18 AWG Insulated Conductors,

Conductors: 18 AWG, 41/34 tinned copper

Insulation: .011" nominal wall of PVC (see color code) .074"

Overall Cable

Cabling: Three conductors twisted together, No Fillers

Binder: .005" Foam Polypropylene tape

Drain Wire: 18 AWG, 41/34 tinned copper

Shield: 36 AWG tinned copper braid, 85% coverage

Jacket: .032" nominal wall of Gray PVC .259"

Color Code

1. Black

2. Red

3. White

Print (Black Inkjet)

3/C 18 AWG E66440 $\text{R}\Delta$ AWM 2464 80C 300V LL41103 CSA AWM
 I/II A/B 80C 300V FT1

Requirements

Temperature: 80C
 Voltage: 300V

Conductors: UL AWM Style 1873

Cable: UL AWM Style 2464
 CSA AWM, FT1
 Materials are RoHS Compliant
 (2011/65/EU & EU 2015/863)

Written By:	rjc	5/21/2009	Rev. 0	Initial Issue
Revised By:	scs	6/19/2009	Rev. 1	Added JM and Referenc Part Numbers
Revised By:	scs	2/23/2022	Rev. 2	Added Print Method and Color, Updated RoHS Statement
Revised By:				