

GENERAL PRODUCT SPECIFICATION Phone 800-316-8877 Fax 978-368-1275 www.jamesmonroewire.com

Description: Two Conductor Cable **Date:** 8/8/2011

Overall PVC Jacket

JM Part Number: JM56417

Reference: TBD

<u>Components</u> Two 16 AWG Conductors

Conductors: 16 AWG, 26/30 bare copper .058"

Insulation: .016" nominal wall of PVC (see color code) .090"

Jacket: .005" nominal wall of Clear Nylon .100"

Overall Cable

Cabling: Two conductors twisted together, no fillers

Binder: Fleece Tape

Jacket: .0495" nominal wall of pressure extruded Black PVC .303"

Print

E66498 2/C 16 AWG (1.31MM2) (UL) MTW 600V OR AWM 2587 90C 600V

VW-1 --- LL41103 CSA AWM I/II A/B 90C 600V FT1

Color Code

Black and Numbered: "1-ONE" and "2-TWO"

Requirements

Temperature: 90°C Approvals: UL MTW

Voltage: 600V UL AWM Style 2587

CSA AWM, FT1

Written By:	scs	8/8/2011	Rev. 0	Initial Issue
Revised By:	scs	10/19/2011	Rev. 1	Add Cust P/N, Rev Ins & Jkt Wall thickness, Rev Ins & Jkt OD's, Rev Print & Approvals
Revised By:				
Revised By:				