



Marlin Thermocouple Wire, Inc.
 847 Canterbury Road, Westlake, OH 44145
 440-835-1950 • 800-686-5818 • 440-835-2188 Fax
 www.marlintcwire.com

Specification

Marlin Thermocouple Wire Part Number: JX-20S-TT

This specification covers a two-conductor duplex, Extension Grade, Standard Limits, Type J 20 awg stranded (7/28), insulated with FEP on the singles, laid parallel and jacketed with FEP. ANSI color code.

Conductor:

Size: 20 Awg Stranded
 Stranding: 7 strands of 28 awg concentric lay
 Nominal OD: .038"
 Positive Leg: JP Fe
 Negative Leg: JN CuNi

Insulation:

Material: Extruded FEP, 400°F
 Nominal Wall: .008"
 Nominal OD: .054"
 Color Code: (+) White, (-) Red

Jacket:

Material: Extruded FEP, 400°F
 Nominal Wall: .010"
 Nominal Diameter: .074" X .128"
 Color: Black

Lengths:

1,000 feet per reel +/- 10% or customer specified

Note: This document is company confidential and cannot be reproduced without the expressed written consent of Marlin Thermocouple Wire, Inc.

Revision #	Description	Date	By	Approved
Initial Rel	Initial Release	02/20/2019	JAG	JAG