

# SIS XHHW-2



## FEATURES

- Special stranding and packaging are available upon request.
- Custom print available upon request.
- UL Listed CSA certified

## APPLICATIONS

- SIS for power and control circuits in control panels and switchboards as per NEC
- XHHW-2 for power control as per NEC

## CONSTRUCTION

Annealed bare or tinned stranded copper conductor insulated with a high grade XLPE, UL Listed, SIS 90°C Dry XHHW-2 90°C Dry 90°C Wet 600 Volts VW-1 meets UL 44.

## OPERATING TEMPERATURE

-40°C to 90°C

# SIS XHHW-2



GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm		
12	65/010	0.030	0.76	0.156	3.96	5000	28
10	104/010	0.030	0.76	0.181	4.60	5000	43
8	7/19/0112	0.045	1.14	0.262	6.65	1000	74
6	7/19/0140	0.045	1.14	0.302	7.67	1000	107
4	7/19/0177	0.045	1.14	0.354	8.99	500	163
2	19/7/0223	0.045	1.14	0.434	11.02	500	235
1/0	19/56/010	0.065	1.65	0.545	13.84	500	391
2/0	19/70/010	0.065	1.65	0.595	15.11	500	482
3/0	19/88/010	0.065	1.65	0.652	16.56	500	597
4/0	19/111/010	0.065	1.65	0.717	18.21	500	743

Please contact your Kalas representative to discuss ampacity and voltage drop values based on NEC standards.

**KALAS HEADQUARTERS**  
167 Greenfield Road  
Lancaster, PA 17601

**WEST COAST OPERATION**  
1678 Delta Court  
Hayward, CA 94544

**KALASWIRE.COM**  
P 717.336.5575  
F 717.945.1002