



# Specification Sheet

## Lake Cable Part #: HW1810/30-04NJ

**Description:** 18 AWG 10 conductor bundled Hoistway cable. All conductors insulated with PVC and rated to 60C 600V

- 1. Conductor**
  - 1.1.AWG Size & Stranding: 18 AWG 16 Strands Class K
  - 1.2.Material: Annealed Bare Copper
  - 1.3. Conductor Count: 10 Conductors
- 2. Insulation**
  - 2.1.Material: PVC
  - 2.2.Wall Thickness: 0.030"
  - 2.3.Diameter: 0.106" ± 0.002"
  - 2.4.Color Code: Yellow with Numerical Print 1 – 10
- 3. Cable Assembly**
  - 3.1.Lay Length: 5.50" LHL, Nominal
  - 3.2.Binder: Helically Applied Polyester Thread
  - 3.3.Bundled Diameter: 0.383" ± 0.030", Nominal
- 4. Markings**
  - 4.1.Type: Conductors permanently identified via surface inkjet print every FOOT
  - 4.2.Legend: LAKE CABLE E525775-01 18AWG C(UL)US HOISTWAY CABLE 600V 60C FT1 ---
  - 4.3.Wire Marking: Numerical Print at End of Print Legend
- 5. Standards**
  - 5.1.UL & C(UL) listed Hoistway Cable per UL Standard 62
  - 5.2.Operating Temperature: -40C to 60C
  - 5.3.Operating Voltage: 600V RMS
  - 5.4.Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive
  - 5.5.Cable is REACH compliant per Regulation (EC) No 1907/2006 (224) Updated January 14, 2023
  - 5.6.Made in the USA
  - 5.7.⚠️ **WARNING:** This product may contain chemicals, such as Vinyl Chloride, known to the state of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). Wash hands after handling

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

---

Signature

---

Company

---

Date

**ALL SPECIFIED PARAMETERS WITHOUT A TOLERANCE ARE NOMINAL AND SUBJECT TO VERIFICATION. LAKE CABLE IS NOT RESPONSIBLE FOR UNKNOWN PERFORMANCE ATTRIBUTES THAT WERE NOT MADE KNOWN TO LAKE CABLE AT THE TIME OF DESIGN.**