



# Specification Sheet

## Lake Cable Part #: SP184C(19)/X-00

**Description:** 18 AWG 4 conductor 19 strand bare copper wire, plenum rated PVC insulation, unshielded, with an overall plenum rated PVC jacket

### 1. Conductor

- 1.1. AWG Size & Stranding: 18 AWG 19 Strands Class C
- 1.2. Material: Annealed Bare Copper
- 1.3. Conductor Count: 4 Conductors

### 2. Insulation

- 2.1. Material: Plenum Rated Polyvinylchloride
- 2.2. Wall Thickness: 0.008"
- 2.3. Diameter: 0.063" ± 0.002"
- 2.4. Color Code: Black #1 (White Ink), Red #2 (Black Ink), White #3 (Black Ink), Pink #4 (Black Ink)

### 3. Assembly

- 3.1. Nominal Lay Length: 2.25" LHL (5.33 Tw/Ft)

### 4. Jacket

- 4.1. Material: Plenum Rated Polyvinylchloride
- 4.2. Wall Thickness: 0.016"
- 4.3. Diameter: 0.192" ± 0.005"
- 4.4. Color: Black
- 4.5. Ripcord: Yes
- 4.6. Weight: 35 Lbs/Mft

### 5. Markings

- 5.1. Type: Cable shall be permanently identified via surface inkjet print
- 5.2. Legend: LAKE CABLE E171202 18AWG 4C 75C (UL) CL3P OR FPLP OR C(UL)US CMP FT6 "ROHS COMPLIANT" MADE IN USA
- 5.3. Footage Markers: Yes

### 6. Electricals

- 6.1. Impedance: 59 Ω ± 10%
- 6.2. Capacitance: 32 pF/ft ± 10%
- 6.3. DC Resistance: 5.67 Ω/Mft @ 20°C

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

---

Signature

---

Company

---

Date



## Specification Sheet

Lake Cable Part #: SP184C(19)/X-00

### 7. Standards

- 7.1. Cable suitable for installation under NEC (NFPA 70) articles 800, 725 and 760 guidelines
- 7.2. Cable suitable for installation in Canada under Section 60 of CEC, Part I
- 7.3. C(UL)US listed as CMP per UL standard 444 and per CSA C22.2 No. 214-17
- 7.4. UL listed as CL3P per UL standard 13 or FPLP per UL standard 1424
- 7.5. Cable meets NFPA 262 (Steiner tunnel) flame test
- 7.6. Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive
- 7.7. Cable is REACH compliant per Regulation (EC) No 1907/2006 (233) Updated January 17, 2023
- 7.8. Operating Voltage: 300V RMS
- 7.9. Made in the USA
- 7.10. ⚠️ WARNING: This product may contain chemicals, such as Vinyl Chloride, known to the state of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). Wash hands after handling

**ALL SPECIFIED PARAMETERS WITHOUT A TOLERANCE ARE NOMINAL AND SUBJECT TO VERIFICATION. LAKE CABLE IS NOT RESPONSIBLE FOR UNKNOWN PERFORMANCE ATTRIBUTES THAT WERE NOT MADE KNOWN TO LAKE CABLE AT THE TIME OF DESIGN.**

