

middleatlantic.com

Ultra-bright Decora® light illuminates component faces

Features

- Mounts into any Decora® style opening
- LED light assembly extends from unit for illumination of rackmount components
- Jumper available for "daisy-chaining" multiple units
- UL Listed plug-in power supply included





Architects' and Engineers' Specifications

Decora® Mount Component Light shall be Middle Atlantic Products model #LT-DEC. Unit shall fit in any standard Decora® sized opening. Light shall contain three white, ultra-bright LED lights. Light assembly shall extend and illuminate when pressed. Light shall automatically switch off when returned to the closed position. Unit shall have a maximum current draw of 70 ma and include two 12V DC power supply jacks (one in, one out), allowing multiple units to be powered by one power supply. Decora® Mount Component Light shall include UL Listed plug-in power supply. Unit shall feature a durable plastic housing with flat black finish. Unit shall be warrantied to be free from defects in material or workmanship under normal use and conditions for a period of 3 years.

OPTIONS

- Middle Atlantic Products model # DECP-1X__(1,2,3,4) shall be a one rackspace Decora® panel and shall accommodate ___ Decora® style components such as LT-DEC
- Single rackspace panel, Middle Atlantic Products model # LT2P shall include two LT-DEC units and be available in black powdercoat finish. Power supply and jumper included
- Single rackspace panel, Middle Atlantic Products model # LT2-T1P shall include two LT-DEC units and one TEMP-DEC temperature display and shall be available in black powdercoat finish. Power supply and jumper included
- 18 inch, 12V DC power jumper shall allow "daisy-chaining" of multiple units. Model # JDC-12X18

electronic version available at middleatlantic.com

Engineered Mounting Solutions

LT-DEC Series basic dimensions

