


LUTZE TOP-T Fittings PG

Metal PG



Characteristics

- Integrated strain relief
- Anti-twist design
- Wide sealing and clamping range
- Easy to install

Specifications

| | |
|-------------------|------------------------------------|
| Connecting thread | PG DIN 40430 |
| Temperature range | |
| Permanent | -20°C - +100°C / -4°F - +212°F |
| Intermittent | -40°C - +150°C / -40°F - +302°F |
| Protection class | IP68 EN 60529 |
| Material | |
| Body | Brass, nickel plated |
| Seal | CR Chloroprene |
| O-ring | Rubber |
| | NBR |

| Part No. | Thread | Clamping Range Ø inches | Clamping Range Ø mm | TL mm | SW1 mm | SW2 mm | H mm | UL R / L |
|--------------------|---------|-------------------------|---------------------|-------|--------|--------|------|----------|
| PG | | | | | | | | |
| FMPG7 | PG 7 | 0.118-0.256 | 3-6.5 | 6 | 14 | 14 | 22 | R |
| FMPG9 | PG 9 | 0.157-0.315 | 4-8 | 6 | 17 | 17 | 23.5 | R |
| FMPG11 | PG 11 | 0.197-0.394 | 5-10 | 6 | 20 | 20 | 26 | R |
| FMPG13 | PG 13.5 | 0.236-0.472 | 6-12 | 6.5 | 22 | 22 | 24.5 | L |
| FMPG16 | PG 16 | 0.394-0.551 | 10-14 | 6.5 | 24 | 24 | 28 | L |
| FMPG21 | PG 21 | 0.512-0.709 | 13-18 | 7.2 | 30 | 30 | 32.5 | L |
| FMPG29 | PG 29 | 0.709-0.984 | 18-25 | 8 | 40 | 40 | 38.5 | L |
| FMPG36 | PG 36 | 0.866-1.260 | 22-32 | 9 | 50 | 50 | 48 | L |
| FMPG42 | PG 42 | 1.181-1.496 | 30-38 | 12 | 58 | 58 | 48.5 | L |
| FMPG48 | PG 48 | 1.339-1.732 | 34-44 | 14 | 64 | 64 | 53 | L |
| LONG THREAD | | | | | | | | |
| FMPG7-L | PG 7 | 0.118-0.256 | 3-6.5 | 10 | 14 | 14 | 22 | R |
| FMPG9-L | PG 9 | 0.157-0.315 | 4-8 | 10 | 17 | 17 | 23.5 | R |
| FMPG11-L | PG 11 | 0.197-0.394 | 5-10 | 10 | 20 | 20 | 26 | R |
| FMPG13-L | PG 13.5 | 0.236-0.472 | 6-12 | 10 | 22 | 22 | 26.5 | L |
| FMPG16-L | PG 16 | 0.394-0.551 | 10-14 | 10 | 24 | 24 | 28 | L |
| FMPG21-L | PG 21 | 0.512-0.709 | 13-18 | 12 | 30 | 30 | 32.5 | L |
| FMPG29-L | PG 29 | 0.709-0.984 | 18-25 | 12 | 40 | 40 | 38.5 | L |

Item Specific Approvals

- UL Recognized (R) or UL Listed (L), as per table
- Type 4X for UL Listed items

Locknuts sold separately.

Specifications are subject to change without prior notice