

LUTZE Cablefix® X

Cablefix® X Cable Entry System



Characteristics

- Cables install easily by pushing the end through the seal from the front
- Integrated seal protects up to UL Type 4X, 12, 13, IP65
- Easy to install: can be bolt mounted with provided hardware or snapped directly into enclosures with a 1.5mm wall thickness
- Entry points are sealed by default, eliminating the need for blanking plugs
- Mounting hardware is included with all frames

Specifications

Frame material	Polyamide (PA) with glass fiber reinforcement
Seal material	Butyl (IIR) rubber
Spacer	Chloroprene
Inner membrane	Polyurethane
Temperature range	-40°C to +80°C -40°F to +176°F
Burning behavior	HB according to UL 94
Silicone free	Yes
Protection class	UL Type 4X* UL Type 12 UL Type 13 IP65
Gasket	Polyurethane
Frame Color	Black RAL 9005

*Note: UL Type 4x applies to cables with a diameter of 5.0mm and larger.

Part No.	Type	Dimensions (WxHxD) mm	Cut out W x H mm	Number of Cables x Cable OD - Ø mm
----------	------	-----------------------	------------------	------------------------------------

Bolt-Mounted Design (for all enclosures)

606550	12	148.0 x 60.0 x 13.5	112 x 36	12 x 5.0-13.0
606551	23	148.0 x 60.0 x 13.5	112 x 36	23 x 4.0-8.5

Snap-in Design (for enclosures with 1.5mm wall thickness)

606561	12	148.0 x 60.0 x 13.5	112 x 36	12 x 5.0-13.0
606562	23	148.0 x 60.0 x 13.5	112 x 36	23 x 4.0-8.5