

# LUTZE DRIVEFLEX® XLPE (C) PVC, Shielded

## Flexible VFD Cable XHHW-2 with UL/TC-ER-JP/WTTC/CE Approvals



### Application

- Shielded motor supply cable to connect power to 3-phase motors, VFD's and Servo Drives
- Cable design for harsh industrial environments and operating conditions with high noise levels
- Thermoset XLPE offering superior overload and short-circuit temperature
- Type XHHW-2 insulation offering smaller ODs for general VFD applications
- Compliant with **NFPA 79** for wiring of industrial machinery
- **TC-ER-JP** for use with cable trays **without conduit**, which can reduce installation costs in industrial environments per NEC 336.10 (7)
- WTTC – wind turbine tray cable rating for use in wind power generation
- Dry, damp or wet conditions

### Characteristics

- Flexible XLPE conductor design
- Reduced cable OD's
- High insulation resistance
- Low capacitance cable
- Effective dual layer shield for EMC compliance
- Specially formulated jacket for oil resistance and easy strip design
- Sunlight resistant
- Direct burial
- Talc and Silicone free

### Technical Data

Voltage	600V 90C UL TC-ER-JP 1000V 90C Flexible VFD Servo Cable, 1000V 105C AWM 1000V WTTC
Temperature	-40°C - +105°C static
Bending radius	6 x cable OD
Conductor marking	Black with white numbers and one green/yellow ground
Oil resistance	Oil Res I/II
Approvals	UL Type Flexible VFD Servo Cable, TC-ER-JP*, WTTC, DP-1 Class I, II Div. 2 per NEC Art. 336, 392, 501, 502 Joist Pull per NEC 336.10(9)* AWM 20886 Submersible Pump (≥ AWG14) c(UL) TC, CIC FT4 UL 1277 Wet/Dry RoHS, REACH

### Construction

- AWG conductor
- Flexible fine wire stranded tinned copper conductors for improved electrical characteristics and reduced oxidation
- XLPE insulation XHHW-2, Wet/Dry
- Shielded with foil tape, tinned copper braid with ≥ 80% optical coverage, and drain wire
- Oil resistant PVC jacket
- Black jacket RAL 9005

Specifications are subject to change without prior notice  
\* JP starting productions 3/2017

Part No.	Description No. of conductors incl. ground	OD / Ø ca. mm	OD / Ø inches	Weight Lbs/Mft	Copper Lbs/Mft
<b>AWG 18 (19/30)</b>					
<b>A1061804</b>	AWG18/04C	10.5	0.415	108	42
<b>AWG 16 (26/30)</b>					
<b>A1061604</b>	AWG16/04C	10.8	0.425	124	54
<b>AWG 14 (41/30)</b>					
<b>A1061404</b>	AWG14/04C	11.6	0.456	154	76
<b>AWG 12 (65/30)</b>					
<b>A1061204</b>	AWG12/04C	13.0	0.51	208	118
<b>AWG 10 (105/30)</b>					
<b>A1061004</b>	AWG10/04C	16.5	0.650	320	183
<b>AWG 8 (168/30)</b>					
<b>A1060804</b>	AWG8/04C	20.6	0.81	478	279

"Small diameter general purpose VFD cable for applications with space restrictions such as conduit installations".

