

LÜTZE SUPERFLEX® PROFIBUS (C) PUR, Shielded

High Flexing PROFIBUS Cable with UL Approval



Application

- For the cabling of industrial field bus systems like PROFIBUS DP, SINEC L2, F.I.P.
- For continuous flexing applications in C-tracks or free movement in automation technology, transport and conveyor technology machine tool manufacturing

Characteristics

- High active and passive interference resistance (EMC)
- Talc and Silicone free

Technical data

Impedance	150Ω ± 15Ω
Loop resistance	<133Ω/km
Operating capacitance	<30pF/m
Rated voltage	300V (max. value)
Test voltage	1,500V, 50Hz
Temperature range	Moving -30°C - +70°C Fixed -40°C - +80°C
Minimum bending radius	Moving 7.5 x cable OD Fixed 5 x cable OD Moving Fast Connect 15 x cable OD Fixed Fast Connect 7.5 x cable OD
Burning behavior	Flame retardant per CSA FT1, UL 1581 VW-1 Flame test IEC 60332-1
Approvals	cULus CMX UL AWM 21198 300V 80C RoHS REACH

Construction

- AWG conductor
- Bare copper wire
- Special polyolefin conductor insulation
- Inner jacket versions with fast assembly FC
- ST static foil shield
- Tinned copper wire braid, optical coverage ≥ 85 %, for 104287 optical coverage ≥ 70 %
- Special PUR
- Violet jacket RAL 4001

Part No.	Description No. of conductors	OD / Ø ca. mm	OD / Ø inches	Weight Lbs/Mft	Copper Lbs/Mft
----------	----------------------------------	---------------------	------------------	-------------------	-------------------

PROFIBUS, UL/CMX

104265	(1x2xAWG24/19) RD, GN	8.0	0.315	37	16
--------	--------------------------	-----	-------	----	----

PROFIBUS, Fast Connect UL/CMX

104287	(1x2xAWG24/19) RD, GN	8.0	0.315	54	20
--------	--------------------------	-----	-------	----	----

PROFIBUS, ET200 UL/CMX

104275	((1x2xAWG24/19)ST+3x0.75)C RD/GN, BU, BK, GNYE	9.8	0.386	97	44
--------	---	-----	-------	----	----