

LUTZE SILFLEX® Tray-ER Blue PVC, Unshielded

Flexible Control and Tray Cable with Blue Conductors for 24V Applications



Application

- Multi-conductor cable for tray applications, with exposed run (open wiring) approval
- Machine tools, machine and plant construction, HVAC technology, assembly and production lines, and other industrial applications
- Compliant with NFPA 79 requirements
- Blue conductors indicating 24 Volt circuits
- MTW for machine tool wiring
- TC-ER for use with cable trays without conduit, which can reduce installation costs in industrial environments
- Dry, damp and wet conditions

Characteristics

- Crush impact resistant
- Gas/vapor-tight sheath per UL 1277
- Non-wicking fillers
- Sunlight resistant
- Flame retardant
- Direct burial
- Talc and silicone free

Technical Data

Voltage	600V 90C TC-ER 600V MTW
Temperature range	-40°C - +90°C static
Bending radius min	4 x cable OD
Conductor marking	Blue with white numbers; and one green/yellow ground; No. 2 is white with a blue stripe *only two blue with white numbers and one green/yellow ground, no white with a blue stripe
Oil resistance	Oil Res I
Approvals	UL Type TC-ER UL/CE (UL) Type MTW or DP-1 Meets NEC 336, 392 Class I & II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 c(UL) TC and CIC FT4 UL1277 RoHS, REACH

Construction

- AWG conductor
- Flexible fine wire stranded bare copper conductors
- PVC/Nylon insulation
- Oil resistant PVC jacket
- Gray jacket similar to RAL 7001

Specifications are subject to change without prior notice

Part No.	Description No. of conductors incl. ground	OD / Ø ca. mm	OD / Ø inches	Weight Lbs/Mft	Copper Lbs/Mft
AWG 18 (19/30)					
A3251803	AWG18/3C*	7.3	0.288	47	18
A3251805	AWG18/5C	8.6	0.337	69	30
A3251807	AWG18/7C	9.4	0.370	89	42
A3251812	AWG18/12C	12.0	0.474	143	72
A3251819	AWG18/19C	14.9	0.588	219	108
A3251825	AWG18/25C	17.4	0.686	295	150
A3251837	AWG18/37C	19.9	0.782	410	223
AWG 16 (26/30)					
A3251603	AWG16/3C*	7.9	0.312	58	25
A3251605	AWG16/5C	9.2	0.364	91	41
A3251607	AWG16/7C	10.1	0.398	116	57
A3251612	AWG16/12C	13.9	0.547	194	98
A3251619	AWG16/19C	16.2	0.638	271	155
A3251625	AWG16/25C	18.9	0.746	379	204
AWG 14 (41/30)					
A3251403	AWG14/3C*	8.9	0.352	82	39
A3251404	AWG14/4C	9.8	0.384	103	52
AWG 12 (65/30)					
A3251204	AWG12/4C	10.9	0.428	137	85
A3251205	AWG12/5C	12.4	0.488	183	105

"Blue conductors are used to indicate 24V DC circuits. The cable is rated 600V TC-ER to permit installation alongside other type TC cables".

