



Specification Sheet

Lake Cable Part #: AVLUTGCC4P

Description: Three element composite cable with an overall plenum rated jacket control cable for lutron 4000/7000 Grafik Eye Systems

(2C) 12 AWG stranded bare copper unshielded with plenum rated PVC Insulation
(1C) 18 AWG stranded bare copper unshielded with plenum rated PVC Insulation
(2C) 22 AWG stranded bare copper twisted shielded pair with FEP Insulation

Element 1: (Power/Control) 12 AWG 2 Conductors Unshielded

- 1. **Conductor**
 - 1.1. AWG & Stranding: 12 AWG 19 Strands Class C
 - 1.2. Material: Annealed Bare Copper
 - 1.3. Conductor Count: 2 Conductors
- 2. **Insulation**
 - 2.1. Material: Plenum Rated Polyvinylchloride
 - 2.2. Wall Thickness: 0.010"
 - 2.3. Color Code: Black, Red

Element 2: (Control) 18 AWG 1 Conductor Unshielded

- 3. **Conductor**
 - 3.1. AWG & Stranding: 18 AWG 7 Strands Class B
 - 3.2. Material: Annealed Bare Copper
 - 3.3. Conductor Count
- 4. **Insulation**
 - 4.1. Material: Plenum Rated Polyvinylchloride
 - 4.2. Wall Thickness: 0.008"
 - 4.3. Color Code: Orange

Element 3: (Data/Communications) 22 AWG 1 twisted shielded pair

- 5. **Conductor**
 - 5.1. AWG & Stranding: 22 AWG 7 Strands Class B
 - 5.2. Material: Annealed Bare Copper
 - 5.3. Conductor Count: 2 Conductors
- 6. **Insulation**
 - 6.1. Material: Fluorinated Ethylene Propylene
 - 6.2. Wall Thickness: 0.010"
 - 6.3. Color Code: White, Violet
- 7. **Assembly**
 - 7.1. Pair Lay Length: 1.5" LHL (8.0 tw/ft)
 - 7.2. Pair Shield: Aluminum/Mylar Tape - 100% Coverage
 - 7.3. Pair Drain Wire: 24 AWG, 7 Strand Tinned Copper



Specification Sheet

Lake Cable Part #: AVLUTGCC4P

8. Nominal Electrical Characteristics for Element 3

- 8.1. Impedance: $62 \Omega \pm 5$
- 8.2. Capacitance: 24 pF/ft
- 8.3. DC Resistance: $14.8 \Omega/\text{Mft}$ @ 20°C

Overall Cable Assembly

9. Assembly - Elements 1 thru 3

- 9.1. Cable Lay Length: 6.00" LHL Nominal (2 Tw/Ft)

10. Jacket

- 10.1. Material: Plenum Rated Polyvinylchloride
- 10.2. Wall Thickness: 0.015"
- 10.3. Diameter: 0.242"
- 10.4. Color: Natural w/Blue Stripe
- 10.5. Ripcord: Yes
- 10.6. Weight: 74 Lbs/Mft

11. Markings

- 11.1. Type: Cable permanently identified via surface inkjet print
- 11.2. Legend: AVALANCHE, MFG FOR LUTRON GRAFIK EYE SYSTEMS 4000/7000 EXTENDED DISTANCE CABLE SPEC 2C 12AWG, 1PR 22AWG, 1C 18AWG E171202 (UL) CL3P 75°C "ROHS" FT-6
- 11.3. Footage Markers: Yes

12. Standards

- 12.1. Cable suitable for installations under NEC (NFPA 70) article 725 guidelines
- 12.2. UL listed as Type CL3P per UL Standard 13
- 12.3. All materials used in the manufacture of this cable are RoHS compliant
- 12.4. Maximum Operating Voltage: 300V
- 12.5. Made in the USA

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION